

target | T2S

Data Migration Tool File Format Specification

R2026.JUN

22 January 2026

Table of Contents

| | | |
|--------------|---------------------------------------------------------------------------------------------------------------|------------|
| 1 | Introduction | 6 |
| 2 | Technical Specification | 7 |
| 2.1 | Data Record Definition | 7 |
| 2.1.1 | Rows and Columns | 7 |
| 2.1.2 | Header | 7 |
| 2.1.3 | Records..... | 7 |
| 2.1.4 | Record Type..... | 7 |
| 2.1.5 | Record Identification | 8 |
| 2.1.6 | Default Values | 8 |
| 2.2 | Further Details | 9 |
| 2.2.1 | Format Types..... | 9 |
| 2.2.2 | ISO 15022 Interoperability..... | 10 |
| 2.2.3 | Timezones | 10 |
| 2.2.4 | Character Set..... | 10 |
| 2.2.5 | Filenames | 10 |
| 2.3 | Technical Specification of the Excel File | 11 |
| 2.3.1 | Excel Version | 11 |
| 2.3.2 | Restrictions | 11 |
| 2.4 | Technical Specification of the Flat File..... | 12 |
| 2.4.1 | Compliance to RFC 4180 | 12 |
| 2.4.2 | Definition of the CSV Format (RFC 4180) | 12 |
| 2.4.3 | Control Characters | 13 |
| 2.4.4 | Encoding | 13 |
| 2.4.5 | Restrictions | 14 |
| 3 | Format of Structured Files..... | 15 |
| 3.1 | Format of Excel and Flat Files | 15 |
| 3.1.1 | Technical Prerequisites | 15 |
| 3.1.2 | Static Data..... | 15 |
| 3.1.3 | Dynamic Data | 101 |
| 3.2 | Format of "Enriched Files"..... | 143 |
| 3.2.1 | Further Notifications for Static Data records | 143 |
| 3.2.2 | Further Notifications for Free of Payment Settlement Instruction and Pending Instructions records..... | 144 |
| 3.2.3 | Further Notifications for Settlement Restriction records | 146 |
| 3.2.4 | Statistical Information | 147 |
| 3.3 | Format of Delta Files | 148 |

History of releases

| Release | Date | Issues | Status ¹ |
|---------|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------|---------------------|
| 0.0.1 | 27/06/2012 | First draft | draft |
| 0.0.2 | 11/09/2012 | Second draft | draft |
| 0.0.3 | 15/10/2012 | Remarks from first review by FES, FIT considered | draft |
| 1.0.0 | 12/11/2012 03/12/2012 | Remarks from second review considered Remarks from FIT considered | final |
| 1.0.1 | 18/12/2012 | MSG: swapped chapter 2 and 3 | final |
| 1.0.2 | 11/02/2013 | Market feedback | |
| 1.0.3 | 08/03/2013 | Back end interface alignment | |
| 1.0.4 | 18/10/2013 | Final version | |
| 1.2 | 29/04/2014 | CR385, CR386, CR453 and CR454 | |
| 1.2.1 | 19/01/2015 | CR460 | |
| 1.2.2 | 30/01/2015 | CR for DMT documentation alignment | |
| 1.2.3 | 12/03/2015 | CRG meeting of 12 March 2015 where it was agreed to clarify the description of the values to define positive/negative of a restriction type | |
| 1.2.4 | 02/06/2015 | Update of the rules for cash payment-related fields | |
| 1.2.5 | 02/03/2016 | CR495 – CR513 – CR575 – CR599 | |
| 1.2.6 | 30/03/2016 | CR583 issue 10 (PBI-158158) | |
| 1.2.7 | 07/10/2016 | Changes due to CR-593, CR-534 & CR-576 | |
| 1.2.8 | 25/07/2017 | Changes due to CR-645, CR-648 | |

¹ Status value: Draft, Open, Final, Dismiss

| Release | Date | Issues | Status ¹ |
|------------------|-------------------|-------------------------------------------|---------------------|
| 1.2.9 | 30/05/2018 | Changes due to CR-607 | |
| 1.2.10 | 04/02/2019 | Changes due to CR-606 | |
| 1.2.11 | 28/02/2020 | Changes due to CR-658, CR-671 & CR-724 | |
| 1.2.12 | 07/08/2020 | Changes due to CR-713, CR-718 & CR-728 | |
| 1.2.13 | 05/03/2021 | Changes due to CR-744 | |
| R2023.JUN | 10/02/2023 | Changes due to CR-638, CR-795 | |
| R2023.NOV | 22/09/2023 | No changes | |
| R2024.NOV | 20/09/2024 | Changes due to CR-833 | |
| <u>R2026.JUN</u> | <u>22/01/2026</u> | <u>Changes due to CR-863</u> | |

Approval and agreement workflow

| | Team Level | | Area Level | | Project Level | | Agreement | |
|---------|------------|------|------------|------|---------------|------|-----------|------|
| Release | Approver | Date | Approver | Date | Approver | Date | Approver | Date |
| | | | | | | | | |
| | | | | | | | | |

Quality Control

| | Quality Control – Domestic Level | | | | | Quality Control – PMO Level | | | |
|---------|----------------------------------|---------|------|--------|--|-----------------------------|---------|------|--------|
| Release | Degree | Checker | Date | Report | | Degree | Checker | Date | Report |
| | | | | | | | | | |
| | | | | | | | | | |

Applicable documents

| Reference | Object |
|-----------|-----------------------------------------------------------------------|
| 1 [UDFS] | 4CB: T2S User Detailed Functional Specifications, V2.1, 02/12/2015 |

Reference documents

| Reference | Object |
|-----------------------|--------------------------------------------------------------------------------------|
| 1 [DMT Specification] | ECB : Data Migration Tool Requirements and Related Procedures, V1.2.1, 20/01/2015 |

| | |
|---------------------|-----------------------|
| Owner domain | Operational Services |
| Owner module | Data Migration Module |

1 Introduction

Prior to their going-live the Data Migration Tool (DMT) offers CSDs and NCBs the opportunity to load bulk static and dynamic data into T2S. The data is located in Excel or in flat files that are created by the user and submitted to T2S via a web application. The Excel files are used by a human being that manually transfers the data into the spreadsheet whereas the flat files are used by a legacy application that automatically exports the data into the file.

This document specifies the details of the format of the Excel and flat files for T2S data migration. Excel and flat files are available for all interfaces in the same manner. It is not a user handbook that describes the interaction of the users with DMT.

2 Technical Specification

2.1 Data Record Definition

This chapter refers to Excel and the flat file in the same manner.

2.1.1 Rows and Columns

A spreadsheet consists of horizontal rows and vertical columns. The columns identify the attributes and are restricted to a specific data type. There is no mixup of different attributes and data types in one column.

2.1.2 Header

The names of the columns appear in the first row. The names support the user to fill out the form but have no further functionality. DMT identifies the attributes based on the location of the column and does not interpret the column names.

2.1.3 Records

A record is a data structure that contains all parameters for a certain business function. A record spans over several rows. This is due to the fact that a record may contain attributes that are repeatable. The repeated attributes are placed in a separate row just below the initial row in the same column.

2.1.4 Record Type

The record type describes the business function of the record. A file may contain several records of the same record type. A mixture of different record types in one file is not possible.

The record type is indicated with a key word in the upper left corner of the file. Since there is only one record type per file the indication occurs only once. For example:

| Record Type | Record Id | An Attribute |
|-------------|-----------|--------------|
| Party | 1 | aaa |
| | 2 | bbb |

2.1.5 Record Identification

A record is identified with a unique record identifier. The identifier must be unique within the file. It is recommended that the record identifier starts with 1 and is consecutively numbered.

In case the record contains repeatable attributes and spans over several rows the record identifier is repeated in each row of the record. Rows with the same record identifier are located one after the other. These connected rows must not be interrupted by rows with another record identifier. For example:

| Record Type | Record Id | A repeatable Attribute | A non-repeatable Attribute |
|-------------|-----------|------------------------|----------------------------|
| Party | 1 | a1 | c1 |
| | 1 | b1 | |
| | 2 | a2 | c2 |
| | 2 | b2 | |

2.1.6 Default Values

Default values are not used. When a field has no value the Excel field remains empty. For example:

| | | |
|-----|--|-----|
| aaa | | ccc |
|-----|--|-----|

In a flat file the length of a field with no value is 0. For example:

aaa,,ccc

DMT does not provide default values for empty fields. Any input parameter must be stated within the files.

2.2 Further Details

2.2.1 Format Types

The values appear in the format as in the table below:

| Format Type | Excel | CSV ² |
|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| DATE | The format depends on the country and location of the user. | The format is « dd/mm/yyyy » with no timezone indication. Example: "30/06/2015" |
| TIME | The format depends on the country and location of the user. | The format is «hh:mm:ss » with no timezone indication. Times are in 24 hour format. Example: "15:30:59" |
| CHAR (n) | String with exactly n characters. | Same format as Excel. |
| VARCHAR (n) | String with n characters maximum. | Same format as Excel. |
| DEC (p,s) | Floating-point number with maximum p integer places and s decimal places. A dot '.' is used as decimal separator. Due to Excel restriction, cell must be treated as text | Floating-point number with maximum p integer places and s decimal places. A dot '.' is used as decimal separator. |
| NUMERIC (p) | Number with maximum p integer places and no decimal places. | Same format as Excel. |
| BOOLEAN | Possible values: ■ true ■ false | Same format as Excel. |

² The CSV format matches to the Excel format when the regional settings of a Windows PC are „English (Great Britain)“

2.2.2 ISO 15022 Interoperability

In order to ensure the interoperability to the ISO 15022 standard the character set of all fields is restricted to the SWIFT X Character Set (see below).

Exceptions might occur if special chars are required. Character set restrictions will not apply on these fields which are not used in ISO15022 messages (e.g. Distin-
guish Name in Party Technical Address for Party) and will not hamper interoperability.

Exceptions are highlighted in the definition of the related fields.

Some fields are restricted in length. The number of characters and integer places is shorter than in ISO 20022. See [UDFS], chapter 2.2.4, for details.

2.2.3 Timezones

Timezones do not appear in the data. The timezone is considered the actual timezone of Frankfurt. This is either **CET** (GMT+01:00) or, when a daylight saving hour is applied, **CEST** (GMT+02:00).

2.2.4 Character Set

All characters belong to the **SWIFT X Character Set**. The character set is as follows:

a b c d e f g h i j k l m n o p q r s t u v w x y z
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
0 1 2 3 4 5 6 7 8 9
/ - ? : () . , ' +
CR LF Space

2.2.5 Filenames

Any filename is permitted.

Remark:

The filenames of the provided examples contain the record type, e.g. "DMT.SDMG.Party.100". This helps the user to identify the respective example but is not required by DMT. DMT only examines the file content to recognize the record type (see chapter 2.1.4 for details).

2.3 Technical Specification of the Excel File

2.3.1 Excel Version

The Excel files adhere to one single distinct version of Microsoft Office.

Comment [A1]: CR645

Detailed information:

- Version: Microsoft® Office Excel® 2007
- File Extension: xlsx

2.3.2 Restrictions

2.3.2.1 Worksheets

The option that one Excel file may contain several worksheets is not supported. DMT uses only the very first worksheet.

2.3.2.2 Number of Rows

Due to technical limitations the number of rows is restricted.

Detailed information:

- Maximum number of rows: 50.000 ³

³ This number might be further optimised

2.3.2.3 Size Limits

In addition to the number of rows, the uploaded file can not exceed 9 MB.

2.4 Technical Specification of the Flat File

2.4.1 Compliancy to RFC 4180

The flat file has a CSV format that follows closely RFC 4180. The RFC specifies a format that is widely used by many implementations and eases the development of an unload process.

Detailed information:

- File Extension: csv

2.4.2 Definition of the CSV Format (RFC 4180)

- Each row is located on a separate line, delimited by a line break (CRLF). For example:

aaa,bbb,ccc CRLF

zzz,yyy,xxx CRLF

- The last row in the file has no ending line break. For example:

aaa,bbb,ccc CRLF

zzz,yyy,xxx

- Within each row, there are one or more fields, separated by commas. Each row contains the same number of fields throughout the file. Spaces are considered part of a field and are not ignored. The last field in the record is not followed by a comma. For example:

aaa,bbb,ccc

1. Each field may or may not be enclosed in double quotes. If fields are not enclosed with double quotes, then double quotes do not appear inside the fields. For example:

```
aaa,"bbb","ccc" CRLF
```

```
zzz,yyy,"xxx"
```

1. Fields containing line breaks (CRLF), double quotes, and commas are enclosed in double-quotes. For example:

```
aaa,"b CRLF bb",ccc CRLF
```

```
zzz,yyy,xxx
```

1. A double-quote appearing inside a field is escaped by preceding it with another double quote ⁴. For example:

```
"aaa","b""bb", "ccc"
```

The escaping with double-quotes ensures that all data can appear. Quotes, commas and line breaks may be included into the business data.

2.4.3 Control Characters

In order to structure the data in the flat file the following control characters are used:

| | |
|----------------------|------|
| Carriage Return (CR) | 0x0d |
| Line Feed (LF) | 0x0a |

2.4.4 Encoding

The encoding of the flat file is UTF-8 with no Byte Order Mark (BOM).

⁴ Actually character « quote » is not allowed. See chapter 2.2.4 for details. Please note that the CSV format definition is independent from the character set.

2.4.5 Restrictions

2.4.5.1 Number of Rows

Due to technical limitations the number of rows is restricted.

Detailed information:

- Maximum number of rows: 50.000 ⁵

2.4.5.2 Size Limits

In addition to the number of rows, the uploaded file can not exceed 9 MB.

⁵ This number might be further optimised

3 Format of Structured Files

3.1 Format of Excel and Flat Files

See chapter 2.2 for the specification and details of the format types.

3.1.1 Technical Prerequisites

3.1.1.1 Record Type Identifier

Prior to the static and dynamic data appears the record type identifier.

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per File |
|------------------|--------------|-------------|--------------|-----------------------------------------------------------------------------------------------------------------------|-----------------------------------------|-----------------|
| 1 | A | Record Type | VARCHAR (50) | Indicates the business function. The required value can be found in the first line of the chapters 3.1.2.1 - 3.1.3.1. | Occurs in the 2 nd row only. | 1..1 |

3.1.2 Static Data

3.1.2.1 Party Reference Data - New

Record Type: "Party"

~~The record is used to create party reference data.~~

~~Related activities covered:~~

TABLE 1 - ACT.3.1

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|---------------|------------------------------------------------|------------------------------------------------------------------------------------------------------------|-------------------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| | | Group "Party" | | | | 1..1 | |
| 3 | C | Parent-BIC | CHAR (11) | | | | 1..1 |
| 4 | D | Type | Possible values: ■ PMBK ■ CSDP ■ ECSD | Classification of the party: ■ PMBK = Payment bank ■ CSDP = CSD participant ■ ECSD = External CSD | | | 1..1 |
| 5 | E | Opening-Date | DATE | Activation date of a party. | Must be equal or greater than the current date. | | 1..1 |
| 6 | F | Closing-Date | DATE | Closing date of the party. | Must be greater than the Opening Date. | | 0..1 |
| 7 | G | BIC | CHAR (11) | Party-BIC. | | | 1..1 |
| | | Group "Name" | | | | 1..1 | |
| 8 | H | Long-Name | VARCHAR (350) | Long-name. | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|----------------------------------------|--------------|-------------------|-------------|----------------------------------------|---------------------------------------------------------------------------------------|-------------------|------------------|
| 9 | I | Short-Name | VARCHAR(35) | Short-name. | | | 1..1 |
| Group "Address" | | | | | Must occur when Type is 'PMBK' or 'ECSD'. Must not occur when Type is something else. | 0..1 | |
| 10 | J | Street | VARCHAR(70) | Name of the street for the address. | | | 1..1 |
| 11 | K | House-Number | VARCHAR(16) | House number for the address. | | | 1..1 |
| 12 | L | Postal-Code | VARCHAR(16) | Postal code for the address. | | | 1..1 |
| 13 | M | City | VARCHAR(35) | City for the address. | | | 1..1 |
| 14 | N | State-or-Province | VARCHAR(35) | State or the province for the address. | | | 0..1 |
| 15 | O | Country-Code | CHAR(2) | Country code of the address. | | | 1..1 |
| Group "Party-Technical Address" | | | | | 1..10 | | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|--------------------------------------|---------------------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| 16 | P | Technical Address | VARCHAR (256) | Unique technical address of the party (distinguished-name). | ISO15022 interoperability character set restriction does not apply | | 1..1 |
| | | Group "Auto-Collateralisation Rule" | | | May occur only when Type is 'PMBK'. It is used to provide client collateralisation service. This group may only be used by NCBs. | 0..1 | |
| 17 | Q | Collateralisation Procedure | Possible-value: I REPO | Type of collateralisation procedure application. Possible-value: I REPO | When Type is 'PMBK' the value must be 'REPO'. | | 1..1 |
| | | Group "Market-Specific Attributes" | | | | 0..10 | |
| 18 | R | Market-Specific Party Attribute Name | VARCHAR (35) | Name of the market-specific attribute. | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|---------------------------------------|--------------|---------------------------------------|---------------|----------------------------------------------|----------------------------------------------------------|-------------------|------------------|
| 19 | S | Market-Specific Party-Attribute Value | VARCHAR (350) | Value of the market-specific attribute. | | | 1..1 |
| Group "Party-Restriction-List" | | | | | | 0..10 | |
| 20 | T | Restriction-Type | CHAR (4) | List of blocking restrictions. | | | 1..1 |
| 21 | U | Restriction-Valid From-Date | DATE | Valid from date and time of the restriction. | Must be equal or greater than the current date and time. | | 1..1 |
| 22 | V | Restriction-Valid From-Time | TIME | | | | 1..1 |
| 23 | W | Restriction-Valid To-Date | DATE | Valid to date and time of the restriction. | Date and time must occur together. | | 0..1 |
| 24 | X | Restriction-Valid To-Time | TIME | | Must be greater than the Valid From date and time. | | 0..1 |

{CR-863}

3.1.2.2 Technical Address Network Service Link – New

I Record Type: "Technical Address Network Service Link"

The record is used to create a link between a technical address and a network service.

Related activities covered:

TABLE 2 - ~~ACT.3.2~~

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|--------------------------------------------------|--------------|-------------------|--------------|----------------------------------------------------|--------------------------------------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC(10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| Group "Party Identification" | | | | | | 1..1 | |
| 3 | C | Parent-BIC | CHAR(11) | BIC of the System Entity responsible for the party | | | 1..1 |
| 4 | D | Party-BIC | CHAR(11) | BIC of the party | | | 1..1 |
| Group "Technical Address Network Service" | | | | | | 1..1 | |
| 5 | E | Technical-Address | VARCHAR(256) | | ISO15022 interoperability character set restriction does not apply | 1..1 | |
| 6 | F | Network-Service | VARCHAR(35) | | | 1..1 | |

{CR-863}

~~3.1.2.3 Additional Party Market Specific Attributes – New~~

Record Type: "Party Market Specific Attribute"

The record is used to create additional market specific attributes for an existing party.

Related activities covered:

TABLE 3 - ACT.3.3

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------------------------------------|---------------|----------------------------------------------------|----------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| | | Group "Party Identification" | | | | 1..1 | |
| 3 | C | Parent-BIC | CHAR (11) | BIC of the System Entity responsible for the party | | | 1..1 |
| 4 | D | Party-BIC | CHAR (11) | BIC of the party | | | 1..1 |
| | | Group "Market-Specific Attributes" | | | | 1..10 | |
| 5 | E | Market-Specific Party-Attribute Name | VARCHAR (35) | Name of the market-specific attribute. | | | 1..1 |
| 6 | F | Market-Specific Party-Attribute Value | VARCHAR (350) | Value of the market-specific attribute. | | | 1..1 |

{CR-863}

3.1.2.4 Securities Account - New**I Record Type: "Securities Account"**~~The record is used to create a securities account.~~~~Related activities covered:~~

TABLE 4 - ACT.4.1

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|----------------------------|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| | | Group "Securities Account" | | | | 1..1 | |
| 3 | C | Securities Account Number | VARCHAR (35) | Unique securities account number. | | | 1..1 |
| 4 | D | Securities Account Type | Possible values: | <p>Classification of the securities account:</p> <ul style="list-style-type: none"> CSDM CSDP ICSA TOFF CSDO ISSA | | | 1..1 |
| | | | | <ul style="list-style-type: none"> CSDM = CSD mirror account CSDP = CSD participant account ICSA = Inter-CSD account TOFF = T2S technical offset account CSDO = CSD omnibus account | | | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------------|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|-------------------|------------------|
| | | | | ■ ISSA = Issuance-account | | | |
| 5 | E | Opening-Date | DATE | Opening-date-of the-securities-account. | Must be equal or greater than the current date. | | 1..1 |
| 6 | F | Closing-Date | DATE | Closing-date-of-the securities-account. | Must be greater than the Opening Date. | | 0..1 |
| 7 | G | Hold/Release | Possible-values: ■ HOLD ■ RELE | Default setting for specific settlement instruction related to the securities account: ■ HOLD = Hold ■ RELE = Release | | | 1..1 |
| 8 | H | Negative-Position | BOOLEAN | ■ true = The securities account can hold a negative position | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|-------------------------------|--------------|---------------------------|-------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| 9 | I | End-Investor-Account-Flag | Possible values: <ul style="list-style-type: none">I NONEI FOPAI DVFO | Additional flags for the securities account: <ul style="list-style-type: none">I NONE = No account allocationsI FOPA = FOP account allocationsI DVFO = DVP/FOP | | | 1..1 |
| 10 | J | Pricing-Scheme | Possible values: <ul style="list-style-type: none">I SACCI ISIN | Pricing scheme of the customer: <ul style="list-style-type: none">I SACC = Securities accountI ISIN = Security | | | 1..1 |
| Group "Account Holder" | | | | | | | 1..1 |
| 11 | K | Parent-BIC | CHAR-(11) | Represents the party. | | | 1..1 |
| 12 | L | BIC | CHAR-(11) | Represents the party. | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|-------------------------------------------------------------|--------------|-----------------------------------------------------------|----------------------|----------------------------------------------------------|------------------------------------------------|-------------------|------------------|
| Group "Market Specific Securities Account Attribute" | | | | | | 0..10 | |
| 13 | M | Market-Specific Securities Account Attribute-Name | VARCHAR (35) | Name of the market specific attribute. | | | 1..1 |
| 14 | N | Market-Specific Securities Account Attribute-Value | VARCHAR (350) | Value of the market specific attribute. | | | 1..1 |
| Group "Securities Account Restriction" | | | | | | 0..10 | |
| 15 | O | Restriction-Type | CHAR (4) | Code to identify the restriction. | | | 1..1 |
| 16 | P | Valid-From-Date | DATE | Valid from date | Must be equal or | | 1..1 |
| 17 | Q | Valid-From-Time | TIME | and time of the securities account. | greater than the current date and time. | | |
| 18 | R | Valid-To-Date | DATE | Valid to date and time of the securities account. | Must be greater than the Valid | | 0..1 |
| 19 | S | Valid-To-Time | TIME | | From date and time. | | |

{CR-863}

3.1.2.5 Additional Securities Account Market Specific Attributes – New

I Record Type: "Securities Account Market Specific Attribute"

~~The record is used to create additional market specific attributes for an existing securities account.~~

~~Related activities covered:~~

TABLE 5 - ACT.4.3

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|----------------------------------------------------|---------------|-----------------------------------------|----------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| | | Group "Securities Account Identification" | | | | 1..1 | |
| 3 | C | Securities Account Number | VARCHAR (35) | | | | 1..1 |
| | | Group "Market Specific Attributes" | | | | 1..10 | |
| 4 | D | Market Specific Securities Account Attribute Name | VARCHAR (35) | Name of the market specific attribute. | | | 1..1 |
| 5 | E | Market Specific Securities Account Attribute Value | VARCHAR (350) | Value of the market specific attribute. | | | 1..1 |

{CR-863}

~~3.1.2.6 Securities - New~~

~~I Record Type: "Security"~~

~~The record is used to create a security.~~

~~Related activities covered:~~

TABLE 6 - ACT.5.1

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|--------------------|--------------|----------------------------------------------------------------------|-------------------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| | | Group "Securities" | | | | 1..1 | |
| 3 | C | ISIN | CHAR (12) | Actual value for the securities code, (the ISIN for the security). | | | 1..1 |
| 4 | D | GFI-Code | CHAR (6) | Classification of the security according to ISO 10962:2021 standard. | | | 1..1 |
| 5 | E | Issue-Date | DATE | Date from which the settlement is allowed for the security. | | | 1..1 |
| 6 | F | Maturity-Date | DATE | Final maturity or expiry date of the security. | Must be equal or greater than the current date. | | 0..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|-----------------------------------------|--------------|---------------------|--------------------------------------|-------------------------------------------------------------------------------------|-------|-------------------|------------------|
| 7 | G | Issue-Currency | CHAR-(3) | Issue-currency of a security in the system using ISO 4217 standard. | | | 1..1 |
| 8 | H | Country-of-Issuance | CHAR-(2) | Country in which the security is issued. | | | 1..1 |
| Group "Security-Name" | | | | | | 1..1 | |
| 9 | I | Long-Name | VARCHAR-(350) | Long-description of the security according to ISO 18774 standard Part 1 and Part 2. | | | 1..1 |
| 10 | J | Short-Name | VARCHAR-(35) | Short description of the security (FIDS) according to ISO 18774 standard. | | | 1..1 |
| Group "Security-Settlement-Data" | | | | | | 1..1 | |
| 11 | K | Settlement-Type | Possible-values: UNIT FAMT | Type of settlement foreseen for the security: UNIT = Units | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|-------------------------------------------|--------------|------------------------------------------------|---------------|-----------------------------------------------------|-------|-------------------|------------------|
| | | | | I FAMT = Nominal | | | |
| 12 | L | Minimum Settlement-Unit | DEC (14,14) | Minimum settlement-unit for a security. | | | 1..1 |
| 13 | M | Settlement-Mul- tiple-for-Units | DEC (14,14) | Settlement multiple-for-units. | | | 1..1 |
| Group "Deviating Settlement-Unit" | | | | | | 0..10 | |
| 14 | N | Deviating Settle- ment-Unit | DEC (14,14) | Deviating-settle- ment-unit for a se- curity. | | | 1..1 |
| Group "Market-Specific Attributes" | | | | | | 0..10 | |
| 15 | O | Market-Specific Security-Attribute Name | VARCHAR (35) | Name of the mar- ket-specific attrib- ute. | | | 1..1 |
| 16 | P | Market-Specific Security-Attribute Value | VARCHAR (350) | Value of the mar- ket-specific attrib- ute. | | | 1..1 |
| Group "Security-Restriction" | | | | | | 0..10 | |
| 17 | Q | Restriction-Type | CHAR (4) | Reason-type-ap- plied-to-the-secur- ity. | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|--------------------------------|--------|--------------------------------------------|-------------------------------------------------------------|-------------------|------------------|
| 18 | R | Restriction-Valid From-Date | DATE | Valid from date and time of the security: | Must be equal or greater than the current date and time. | | 1..1 |
| 19 | S | Restriction-Valid From-Time | TIME | | | | |
| 20 | T | Restriction-Valid To-Date | DATE | Valid to date and time of the restriction: | Must be equal or greater than the valid from date and time. | | 0..1 |
| 21 | U | Restriction-Valid To-Time | TIME | | | | |

{CR-863}

3.1.2.7 Securities Market Specific Attributes – New

I Record Type: "Securities Market Specific Attribute"

The record is used for two purposes:

1. to let Security Maintenance Entity create additional market specific attributes for an existing security
2. to let Investor CSDs create their own set of market specific attributes for an existing security

Related activities covered:

TABLE 7 - ACT-5.2

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|---------------------------------|--------------|-------------|--------------|----------------------------------|----------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| Group "Security Identification" | | | | | | 1..1 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------------------------------------|---------------|--------------------------------------------------------------------|-------|-------------------|------------------|
| 3 | C | ISIN | CHAR-(12) | Actual value for the securities code, (the ISIN for the security). | | | 1..1 |
| | | Group "Market-Specific Attributes" | | | | 1..10 | |
| 4 | D | Market-Specific Party-Attribute Name | VARCHAR-(35) | Name of the market-specific attribute. | | | 1..1 |
| 5 | E | Market-Specific Party-Attribute Value | VARCHAR-(350) | Value of the market-specific attribute. | | | 1..1 |

{CR-863}

~~3.1.2.8 Investor CSD Security Restrictions – New~~

Record Type: "Investor CSD Security Restrictions"

~~The record is used by Investor CSDs to apply restrictions on securities.~~

~~Related activities covered:~~

TABLE 8 - ACT.5.3

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|--------------|----------------------------------|----------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC-(10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|-------------------------------------|--------------|-----------------------------|----------|--------------------------------------------------------------------|-------------------------------------------------------------|-------------------|------------------|
| Group "Securities" | | | | | | | |
| 3 | E | ISIN | CHAR(12) | Actual value for the securities code, (the ISIN for the security). | | | 1..1 |
| Group "Security-Restriction" | | | | | | | |
| 4 | D | Restriction-Type | CHAR(4) | List of blocking restrictions. | | | 1..1 |
| 5 | E | Restriction-Valid-From-Date | DATE | Valid from date and time of the restriction. | Must be equal or greater than the current date and time. | | 1..1 |
| 6 | G | Restriction-Valid-From-Time | TIME | | | | 1..1 |
| 7 | G | Restriction-Valid-To-Date | DATE | Valid to date and time of the restriction. | Must be equal or greater than the valid from date and time. | | 0..1 |
| 8 | H | Restriction-Valid-To-Time | TIME | | | | |

{CR-809}

~~3.1.2.9 CSD Account Link - New~~

~~I Record Type: "CSD Account Link"~~

~~The record is used to create a link between a technical issuer and a CSD account~~

~~Related activities covered:~~

TABLE 9 - ~~ACT.4.2~~

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|----------------------------------|--------------|-----------------------------------------|-----------------------------------------------------------------|-------------------|------------------|
| 9 | I | CSD-Participant Account | VARCHAR (35) | CSD-participant account number. | Not allowed if "External-CSD-Participant-Account" is specified. | | 0..1 |
| 10 | J | Mirror-Account | VARCHAR (35) | Mirror-account number. | | | 0..1 |
| 11 | K | Inter-CSD-Account | VARCHAR (35) | Inter-CSD-account number. | | | 0..1 |
| 12 | L | Omnibus-Account | VARCHAR (35) | Omnibus-account number. | | | 0..1 |
| 13 | M | External-CSD-Participant-Account | VARCHAR (35) | External-CSD-participant account number | Not allowed if "CSD-Participant-Account" is specified. | | 0..1 |

{CR-863}

3.1.2.10 Securities CSD Link - New**I Record Type: "Securities CSD Link"****The record is used to create a securities CSD link.****Related activities covered:**

TABLE 10 - ACT.6.1

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|----------------------------|------------------------------------------|--------------------------------------------------------------|-------------------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record | 1..n | |
| | | Group "CSD-Link" | | | | 1..1 | |
| 3 | C | ISIN | CHAR (12) | ISIN of the security. | | | 1..1 |
| 4 | D | Link-Type | Possible values: NVST ISSR | Possible values: NVST = Investor ISSR = Issuer | | | 1..1 |
| 5 | E | Valid-From | DATE | Valid from date of the securities CSD link. | Must be equal or greater than the current date. | | 1..1 |
| 6 | F | Valid-To | DATE | Valid to date of the securities CSD link. | Must be greater than the Valid From date. | | 0..1 |
| 7 | G | Issuer/Investor Parent BIC | CHAR (11) | Issuer / investor parent BIC. | | | 1..1 |
| 8 | H | Issuer/Investor BIC | CHAR (11) | Issuer / investor BIC. | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|---------------------------------|--------------|-----------------------------|--------------|---------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|-------------------|------------------|
| 9 | I | Security-Maintenance | BOOLEAN | I 'true' = the involved-CSD (issuer/technical-issuer/investor) is also the maintainer of the related reference-data | | | 1..1 |
| 10 | J | Technical-Issuer Parent-BIC | CHAR-(11) | Technical-issuer parent-BIC. | Both values must occur together. | | 0..1 |
| 11 | K | Technical-Issuer BIC | CHAR-(11) | Technical-issuer BIC. | | | 0..1 |
| Group "Issuance-Account" | | | | | | 0..10 | |
| 12 | L | Issuance-Account | VARCHAR-(35) | Issuance-account number. | | | 1..1 |
| 13 | M | Primary | BOOLEAN | I true = The account is the primary-issuance-account (the one used for realignment-chain) | At least one and only one issuance account must be primary. | | 1..1 |

{CR-863}

3.1.2.11 CMB Securities Account Links – New**I Record Type: "CMB Securities Account Link"**~~The record is used to create a CMB securities account link.~~~~Related activities covered:~~

TABLE 11 - ACT.15.1

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-----------------------------------|--------------|---------------------------------------------------------------|-------------------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| | | | | | | 1..1 | |
| 3 | C | Securities Account Number | VARCHAR (35) | Number of the related securities account. | | | 1..1 |
| 4 | D | T2S-Dedicated Cash Account Number | VARCHAR (34) | DCA of the CMB the securities account number is linked to | | | 1..1 |
| 5 | E | Valid-From | DATE | Valid from date and time of the CMB securities accounts link. | Must be equal or greater than the current date. | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|------------------------|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|-------------------|------------------|
| 6 | F | Valid-To | DATE | Valid-to-date-and time-of-the-CMB securities accounts link. | Must-be-greater than-the-Valid From-date. | | 0..1 |
| 7 | G | Default-Link | BOOLEAN | I true = The T2S dedicated cash account is the default-link-for the securities account. | | | 1..1 |
| 8 | H | Collateralisation Link | BOOLEAN | I true = T2S can use-the-securities,ear-marked-as-collateral-and held-on-the-securities-account, for auto-collateralisation-operations-on-the T2S-dedicated cash-account-it is-linked-to. | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|----------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| 9 | I | Cash-Settlement Link | BOOLEAN | I true = T2S can use the link between the securities account and the T2S dedicated cash account for the settlement of the cash-leg of a settlement instruction. | | | 1..1 |

{CR-863}

3.1.2.12 User—New

I Record Type: "User"

The record is used to create a user.

Related activities covered:

TABLE 12 - ACT.16.1

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|--------------|----------------------------------|----------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|----------------------|--------------|----------------------------|---------------|-------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| Group "User" | | | | | | 1..1 | |
| 3 | C | Login-Name | VARCHAR (35) | Login-name. | | | 1..1 |
| 4 | D | Name | VARCHAR (127) | Name of the user. | | | 1..1 |
| 5 | E | System-User-Ref- erence | VARCHAR (35) | System reference of the user. | | | 1..1 |
| 6 | F | Lockout-From-Date | DATE | Date and time when the user is locked out from the system. | Must be equal or greater than the current date and time. | | 0..1 |
| 7 | G | Lockout-From-Time | TIME | | Date and time can- not be specified when "Lockout" = false. Date and time are mandatory when "Lockout" = true | | 0..1 |
| 8 | H | Lockout | BOOLEAN | I true = The user cannot enter the sys- tem after the Lockout-From Date and Time | | | 1..1 |
| Group "Party" | | | | | | 1..1 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|-----------|-------------------|-------|-------------------|------------------|
| 9 | I | Parent-BIC | CHAR-(11) | Party-parent-BIC. | | | |
| 10 | J | BIC | CHAR-(11) | Party-BIC. | | | 1..1 |

{CR-863}

3.1.2.13 Roles - New

I Record Type: "Role"

The record is used to create a role.

Related activities covered:

TABLE 13 - ACT.16.2

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|------------------|---------------|----------------------------------|---------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC-(10) | Unique identifier of the record. | Must occur in each line of the record | 1..n | |
| | | | | | | 1..1 | |
| 3 | C | Role-Name | VARCHAR-(35) | Name of the role. | | | 1..1 |
| 4 | D | Role-Description | VARCHAR-(127) | Description of the role. | | | 1..1 |

{CR-863}

3.1.2.14 Secured Group - New

I Record Type: "Secured Group"

The record is used to create a secured group.

Related activities covered:

TABLE 14 - ACT.16.3

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|----------------------------------------|--------------|--------------------|------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record | 1..n | |
| Group "Secured-Group" | | | | | | 1..1 | |
| 3 | C | Secured-Group Type | Possible values: PART SECU SACC CASH | Classification for the secured-group: PART = Parties SECU = Securities SACC = Securities Accounts CASH = T2S Dedicated Cash Accounts | | | 1..1 |
| Group "Secured-Object: Parties" | | | | | Occurs only when Secured-Group Type is 'Parties'. | 0..10 | |
| 4 | D | Parent-BIC | CHAR (11) | Parent-BIC of the secured-party objects. | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|---------------------------|--------------|----------------------------------------------------------------------|-----------------------------------------------------------------------|-------------------|------------------|
| 5 | E | BIC | CHAR-(11) | BIC of the secured party objects. | | | 1..1 |
| | | | | Group "Secured-Object: Securities" | Occurs-only-when Secured-Group Type-is-'Securities'. | 0..10 | |
| 6 | F | ISIN | CHAR-(12) | ISIN of the secured security objects. | | | 1..1 |
| | | | | Group "Secured-Object: Securities-Accounts" | Occurs-only-when Secured-Group Type-is-'Securities Accounts'. | 0..10 | |
| 7 | G | Securities Account Number | VARCHAR-(35) | Securities account number of the secured securities accounts object. | | | 1..1 |
| | | | | Group "Secured-Object: T2S-Dedicated-Cash-Accounts" | Occurs-only-when Secured-Group Type-is-'T2S-Dedicated-Cash-Accounts'. | 0..10 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-----------------------------------|--------------|--------------------------------------------------------------------|-------|-------------------|------------------|
| 8 | H | T2S-Dedicated Cash Account Number | VARCHAR-(34) | T2S-dedicated cash account number of the secured security objects. | | | 1..1 |

{CR-863}

3.1.2.15 Grant Roles - New

I Record Type: "Grant Role"

The record is used to grant a role to a party and/or a user.

Related activities covered:

TABLE 15 - ACT.16.4

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|--------------|----------------------------------|---------------------------------------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC-(10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| Group "Role" | | | | | | 1..1 | |
| 3 | C | Role-Name | VARCHAR-(35) | Name of the role to be granted. | | | 1..1 |
| Group "User" | | | | | Mandatory if group "Party" is not specified, Not allowed otherwise. | 0..1 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|----------------------|--------------|-------------|--------------|--------------------------|---------------------------------------------------------------------------|-------------------|------------------|
| 4 | D | User | VARCHAR-(35) | Login-name of the user. | | | 1..1 |
| Group "Party" | | | | | Mandatory if group "User" is not specified. Not allowed otherwise. | 0..1 | |
| 5 | E | Parent-BIC | CHAR-(11) | Parent-BIC of the party. | | | 1..1 |
| 6 | F | BIC | CHAR-(11) | BIC of the party. | | | 1..1 |

{CR-863}

3.1.2.16 Grant System Privilege – New

I Record Type: "Grant System Privilege"

The record is used to grant a system privilege to a party, user or role.

Related activities covered:

TABLE 16 - ACT.16.4

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|--------------|----------------------------------|----------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC-(10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|--------------------------|--------------|-----------------------|---------------------|--------------------------------------|-----------------------------------------------------------------------------|-------------------|------------------|
| | | | | | One-and-only-one of the groups "Role", "Party" or "User" must occur. | 0..1 | |
| Group "Role" | | | | | | | |
| 3 | C | Role-Name | VARCHAR (35) | Name of the role. | | | 1..1 |
| | | | | | One-and-only-one of the groups "Role", "Party" or "User" must occur. | 0..1 | |
| | | | | | | | |
| Group "Party" | | | | | | | |
| 4 | D | Parent-BIC | CHAR (11) | Parent-BIC of the party. | | | 1..1 |
| 5 | E | BIC | CHAR (11) | BIC of the party. | | | 1..1 |
| | | | | | One-and-only-one of the groups "Role", "Party" or "User" must occur. | 0..1 | |
| Group "User" | | | | | | | |
| 6 | F | User | VARCHAR (35) | Login name of the user. | | | 1..1 |
| | | | | | One-and-only-one of the groups "Role", "Party" or "User" must occur. | 0..1 | |
| Group "Privilege" | | | | | | | |
| 7 | G | Privilege-Name | VARCHAR (35) | Name of the system-privilege. | ISO15022-interoperability-character set-restriction does not apply | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|---------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| 8 | H | Deny-Option | BOOLEAN | <ul style="list-style-type: none"> true = The system privilege is explicitly denied false = The system privilege is explicitly assigned | | | 1..1 |
| 9 | I | 4-Eyes-Option | BOOLEAN | <ul style="list-style-type: none"> true = The 4-eyes principle is required to perform the activity linked to the system privilege false = The 2-eyes principle is required to perform the activity linked to the system privilege | | 1..1 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|----------------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| 10 | 3 | Administration-Op- tion | BOOLEAN | I true = If the grantee of the privilege is a user or a role the grantee is allowed to grant the same privilege to an other user or role of the same party. If the grantee of the privilege is a party, the party adminis- trators of the grantee party are allowed to grant the same privilege also to other parties. | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| | | | | <p>I false = If the grantee of the privilege is a user or a role the grantee is not allowed to grant the same privilege to another user or role of the same party. If the grantee of the privilege is a party, the party administrators of the grantee party are allowed to grant the same privilege only to users and roles of the same party.</p> | | | |

{CR-863}

3.1.2.17 Grant Object Privilege – New

I Record Type: "Grant Object Privilege"

The record is used to grant an object privilege to a party, user or role. Except "Secured Group" all secured element types are covered. For secured element type "Secured Group" see chapter 3.1.2.18.

Related activities covered:

TABLE 17 - ACT.16.4

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-------------|--------------|----------------------------------|----------------------------------------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| | | | | | One and only one of the groups "Role", "Party" or "User" must occur. | 0..1 | |
| 3 | C | Role-Name | VARCHAR (35) | Name of the role. | | | 1..1 |
| | | | | | One and only one of the groups "Role", "Party" or "User" must occur. | 0..1 | |
| 4 | D | Parent-BIC | CHAR (11) | Parent-BIC of the party. | | | 1..1 |
| 5 | E | BIC | CHAR (11) | BIC of the party. | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|--------------------------|--------------|----------------------|------------------|----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| | | | | | One-and-only-one of-the-groups "Role", "Party" or "User" must occur. | 0..1 | |
| Group "User" | | | | | | | |
| 6 | F | User | VARCHAR (35) | Login-name of the user. | | | 1..1 |
| | | | | | | 1..1 | |
| | | | | | | | |
| Group "Privilege" | | | | | | | |
| 7 | G | Secured-Element Type | Possible-values: | Possible-values: I SYSE I PART I SECU I PAAC I SACC I CASH | Possible-values: I SYSE = System Entity I PART = Party I SECU = Security I PAAC = Party and its accounts I SACC = Securities Account I CASH = T2S Dedicated Cash Account | | 1..1 |
| | | | | | | | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|-----------------------------------------------|--------------|-------------------------|--------------|---------------------------------|------------------------------------------------------------------------------------------------|-------------------|------------------|
| Group "Party"/"Party-and-its-accounts" | | | | | Occurs-only-when Secured-Element Type-is-PART (Party)-or-PAAC (Party-and-its-accounts). | 0..1 | |
| 8 | H | Parent-BIC | CHAR-(11) | Parent-BIC of the party. | | | 1..1 |
| 9 | I | BIC | CHAR-(11) | BIC of the party. | | | 1..1 |
| Group "Security" | | | | | Occurs-only-when Secured-Element Type-is-'Security'. | 0..1 | |
| 10 | J | ISIN | CHAR-(12) | ISIN of the security. | | | 1..1 |
| Group "Securities-Account" | | | | | Occurs-only-when Secured-Element Type-is-'Securities Account'. | 0..1 | |
| 11 | K | Security-Account Number | VARCHAR-(35) | Number of the security-account. | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-----------------------------------|--------------|-----------------------------------------------------------|-------------------------------------------------------------------------------|-------------------|------------------|
| | | | | | Occurs-only-when Secured-Element Type-is 'T2S-Dedicated-Cash-Account'. | 0..1 | |
| 12 | L | T2S-Dedicated-Cash-Account-Number | VARCHAR (34) | Number of the T2S dedicated-cash-account. | | | 1..1 |
| | | | | | Occurs-only-when Secured-Element Type-is SYSE (System-Entity) | 0..1 | |
| 13 | M | BIC | CHAR (11) | BIC. | | | 1..1 |
| | | | | | | 1..1 | |
| 15 | N | Privilege-Name | VARCHAR (35) | Name of the object-privilege. | ISO15022 interoperability-character-set-restriction does not apply | | 1..1 |
| 16 | O | Deny-Option | BOOLEAN | I true = The object privilege is explicitly denied | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-----------------------|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| | | | | <ul style="list-style-type: none"> false = The object privilege is explicitly assigned | | | |
| 17 | P | 4-Eyes-Option | BOOLEAN | <ul style="list-style-type: none"> true = The 4-eyes-principle is required to perform the activity linked to the object privilege false = The 2-eyes-principle is required to perform the activity linked to the object privilege | | | 1..1 |
| 18 | Q | Administration-Option | BOOLEAN | <ul style="list-style-type: none"> true = If the grantee of the privilege is a user or a role the grantee is allowed to | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| | | | | <p>grant-the-same privilege-to-an- other-user-or role-of-the same-party. If the-grantee-of the-privilege-is a-party, the party-adminis- trators-of-the grantee-party are-allowed-to grant-the-same privilege-also to-other parties.</p> <p> false = If the grantee-of-the privilege-is-a user-or-a-role the-grantee-is not-allowed-to grant-the-same privilege-to-an-</p> | | | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| | | | | other user or role of the same party. If the grantee of the privilege is a party, the party administrators of the grantee party are allowed to grant the same privilege only to users and roles of the same party. | | | |

{CR-863}

3.1.2.18 Grant Object Privilege (Secured Group) – New

I Record Type: "Grant Object Privilege (Secured Group)"

The record is used to grant an object privilege to a party, user or role. As secured element type only "Secured Group" is covered. For the other secured element types see chapter 3.1.2.17. The record does not refer to an existing secured group. Instead, a new secured group is created.

Related activities covered:

TABLE 18 - ACT:16.4

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-----------------------|--------------|----------------------------------|----------------------------------------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| | | Group "Role" | | | One and only one of the groups "Role", "Party" or "User" must occur. | 0..1 | |
| 3 | C | Role-Name | VARCHAR (35) | Name of the role. | | | 1..1 |
| | | Group "Party" | | | One and only one of the groups "Role", "Party" or "User" must occur. | 0..1 | |
| 4 | D | Parent-BIC | CHAR (11) | Parent BIC of the party. | | | 1..1 |
| 5 | E | BIC | CHAR (11) | BIC of the party. | | | 1..1 |
| | | Group "User" | | | One and only one of the groups "Role", "Party" or "User" must occur. | 0..1 | |
| 6 | F | User | VARCHAR (35) | Login name of the user. | | | 1..1 |
| | | Group "Secured Group" | | | | 1..1 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|--------------------------|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|-------------------|------------------|
| 7 | G | Secured-Group Identifier | NUMERIC (9) | Identifier of the secured-group as get from related U2A-screen. | | | 1..1 |
| | | Group "Administration" | | | | 1..1 | |
| 8 | H | Privilege-Name | VARCHAR (35) | Name of the object privilege. | ISO15022 interoperability-character set-restriction does not apply | | 1..1 |
| 9 | I | Deny-Option | BOOLEAN | <ul style="list-style-type: none"> I true = The object privilege is explicitly denied I false = The object privilege is explicitly assigned | | | 1..1 |
| 10 | J | 4-Eyes-Option | BOOLEAN | <ul style="list-style-type: none"> I true = The 4-eyes-principle is required to perform the | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|----------------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| | | | | <p>activity-linked to-the-object privilege</p> <ul style="list-style-type: none"> I false = The 2-eyes-principle is required to perform the activity-linked to-the-object privilege | | | |
| 11 | K | Administration-Op- tion | BOOLEAN | <ul style="list-style-type: none"> I true = If the grantee of the privilege is a user or a role the grantee is allowed to grant the same privilege to another user or role of the same party. If the grantee of the privilege is a party, the | | 1..1 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| | | | | <p>party-administrators-of-the-grantee-party-are-allowed-to-grant-the-same-privilege-also-to-other-parties.</p> <p> false = If the-grantee-of-the-privilege-is-a-user-or-a-role-the-grantee-is-not-allowed-to-grant-the-same-privilege-to-another-user-or-role-of-the-same-party. If-the-grantee-of-the-privilege-is-a-party, the-party-administrators-of-the</p> | | | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|--------|--------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| | | | | grantee-party are-allowed-to grant-the-same privilege-only to-users-and roles-of-the same-party. | | | |

{CR-863}

3.1.2.19 Message Subscription Rule Set - New

I Record Type: "Message Subscription Rule Set"

The record is used to create message subscription rules and a message subscription rule set and the relationship among the rule set and a list of parties.

Related activities covered:

TABLE 19 - ACT.17.1

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|---------------------------------------|--------------|--------------------------------------------|-------------------------------------------|-------------------|------------------|
| 2 | 8 | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| | | Group "Message Subscription Rule Set" | | | | 1..1 | |
| 3 | € | Name | VARCHAR (35) | Name of the message subscription rule set. | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|--------------------------|--------------|---------------------------------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|-------------------|------------------|
| 4 | D | Description | VARCHAR (350) | Description of the message subscription rule set. | | | 1..1 |
| 5 | E | Valid-From | DATE | Valid from date of the message subscription rule set. | Must be greater than the current date. | | 1..1 |
| 6 | F | Valid-To | DATE | Valid to date of the message subscription rule set. | Must be greater than the Valid From date. | | 0..1 |
| 7 | G | Positive/Negative Parameter Set | BOOLEAN | <ul style="list-style-type: none"> I true = The message subscription rule set must be used in positive way I false = The message subscription rule set must be used in negative way | | | 1..1 |
| Group "Interested Party" | | | | | | 0..10 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|----------|-------------------------------------|-------|-------------------|------------------|
| 8 | H | Parent-BIC | CHAR(11) | Parent-BIC of the interested party. | | | 1..1 |
| 9 | I | Party-BIC | CHAR(11) | BIC of the interested party. | | | 1..1 |

{CR-863}

3.1.2.20 Message Subscription Rule - New

Record Type: "Message Subscription Rule"~~The record is used to create message subscription rules connected to an existing message subscription rule set.~~

I Related activities covered:

TABLE 20 - ACT.17.2

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-----------------|-------------|--------------------------------------------|----------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC(10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| | | | | | | 1..1 | |
| 3 | C | Name | VARCHAR(35) | Name of the message subscription rule set. | | | 1..1 |
| | | | | | | 1..1 | |
| 4 | D | Sequence-Number | NUMERIC(9) | Sequence related to the rule. | | | 1..1 |
| | | | | | | | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|----------------------------------------------------|--------------|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------|---------------------------------------------------------------------------------------------------------|-------------------|------------------|
| 5 | E | Valid-From | DATE | Valid-from-date-of the-message-subscription-rule. | Must-be-greater than-the-current date. | | 1..1 |
| 6 | F | Valid-To | DATE | Valid-to-date-of-the message-subscription-rule. | Must-be-equal-or greater-than-the valid-from-date. | | 0..1 |
| Group "Message Subscription Rule Parameter" | | | | | Each-Message-Sub- scription-Rule-may have-up-to-10-Mes- sage-Subscriptio n-Rule-Parameters. | 1..10 | |
| 7 | G | Group | VARCHAR-(35) | | | | 1..1 |
| 8 | H | Parameter-Type-Name | Name-of-the-parameter-type-to-be-set-for-the-rule. Allowed-values-are: <ul style="list-style-type: none">■ INTP-(Instruction-Type)■ MXST-(Message-Status)■ PART-(PARTY-)■ SACC-(Securities-Account) | | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|-------|-------------------|------------------|
| | | | <ul style="list-style-type: none"> ISIN CASH-(T2S DCA) INST-(Instruc- tion-Status) TRCD-(Trans- action-Code) CURR-(Cur- rency) AMFL-(Already Matched-Flag) MXID-(Mes- sage-Identifi- cation) SECO-(Settle- ment-Transac- tion-Condition Code) BUPA-(Busi- ness-Sending Party) | | | | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| | | | <ul style="list-style-type: none"> ■ BUSE (System User-Reference) ■ INPA (Instructioning Party) | | | | |
| 9 | I | Parameter-Type Value | VARCHAR(35) | Value for the parameter-type | Mandatory when Parameter-Type Name is: INTP, MXST, INST, TRCD, CURR, AMFL, MXID, SECO, BUSE; not allowed otherwise | | 0..1 |
| 10 | J | Parameter-Parent BIC-Identifier | CHAR(11) | | Mandatory when Parameter-Type Name is: PART Not allowed otherwise. | | 0..1 |
| 11 | K | Parameter-Party BIC-Identifier | CHAR(11) | | Mandatory when Parameter-Type Name is: PART | | 0..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-----------------------------------------|-------------|-------------|-----------------------------------------------------------------------------------------------|-------------------|------------------|
| | | | | | Not allowed otherwise. | | |
| 12 | L | Parameter Securities-Account-Identifier | VARCHAR(35) | | Mandatory when Parameter-Type Name is: SACC Not allowed otherwise. | | 0..1 |
| 13 | M | Parameter Securities-Identifier | CHAR(12) | | Mandatory when Parameter-Type Name is: ISIN Not allowed otherwise. | | 0..1 |
| 14 | N | Parameter Cash Account-Identifier | VARCHAR(34) | | Mandatory when Parameter-Type Name is: CASH Not allowed otherwise. | | 0..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|----------------------------------------------------------------|----------|-------------|-----------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| 15 | E | Parameter-Busi- ness-Sending-Par- ent-BIC-Identifier | CHAR(11) | | Mandatory when Parameter-Type Name is: BUPA Not allowed other- wise. | | 0..1 |
| 16 | P | Parameter-Busi- ness-Sending-Party BIC-Identifier | CHAR(11) | | Mandatory when Parameter-Type Name is: BUPA Not allowed other- wise. | | 0..1 |
| 17 | Q | Parameter In- structing-Party Parent-BIC-Identifi- er | CHAR(11) | | Mandatory when Parameter-Type Name is: INPA Not allowed other- wise. | | 0..1 |
| 18 | R | Parameter In- structing-Party Party-BIC-Identifi- er | CHAR(11) | | Mandatory when Parameter-Type Name is: INPA | | 0..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|--------|-------------|-------------------------------|-------------------|------------------|
| | | | | | Not allowed otherwise. | | |

{CR-863}

3.1.2.21 Restriction Type - New

~~Record Type: "Restriction Type"~~

~~The record is used to create a restriction type.~~

I Related activities covered:

TABLE 21 - ACT.18.1

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|---------------------------------|--------------|------------------|---------------|------------------------------------------|-------------------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| Group "Restriction Type" | | | | | | 1..1 | |
| 3 | C | Restriction-Type | CHAR(4) | Restriction-type code. | | | 1..1 |
| 4 | D | Description | VARCHAR (350) | Description of the restriction-type. | | | 1..1 |
| 5 | E | Valid-From | DATE | Valid-from date of the restriction type. | Must be equal or greater than the current date. | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|-------------------|------------------|
| 6 | F | Valid-To | DATE | Valid-to-date-of the restriction-type. | Must-be-greater than-the Valid From-date. | | 0..1 |
| 7 | G | Object-Restriction Type | Possible-values: | Possible-values: | | | 1..1 |
| | | | <ul style="list-style-type: none"> CBAL XACC PART SECU SACCSPOS SETT INPM INBM SYSE CASH | <ul style="list-style-type: none"> CBAL = Cash balance XACC = External RTGS account PART = Party SECU = Security SACC = Securities account SPOS = Securities position SETT = Settlement instruction | | | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-----------------------------|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| | | | | <ul style="list-style-type: none"> ■ INPM = Intra-Position-Movement-Instructions ■ INBM = Intra-balance-Movement-Instructions ■ SYSE = System entity ■ CASH = T2S Dedicated-cash account | | | |
| 8 | H | Restriction-Processing-Type | Possible-values: | <p>Possible-values:</p> <ul style="list-style-type: none"> ■ BALA ■ BLCK ■ COLL ■ COSD ■ VAHO ■ DELI ■ REJE | <p>Possible-values:</p> <ul style="list-style-type: none"> ■ BALA = Balance-Type-/Earmarking ■ BLCK = Blocking ■ COLL = Collateralized ■ COSD = CoSD Blocking | 1..1 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------------------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|-------------------|------------------|
| | | | I RESE | <ul style="list-style-type: none"> I VAHO = CSD Validation Hold I DELT = Deliverable I REJE = Rejection I RESE = Reservation | | | |
| 9 | I | Currency | CHAR(3) | | Must occur when the Restriction Processing Type is 'Earmarking for Auto-collateralization'. | 0..1 | |
| 10 | J | Positive / Negative BOOLEAN Parameter Set | BOOLEAN | <ul style="list-style-type: none"> I true = the restriction is applied if the rules are satisfied.. | | 1..1 | |

{CR-863}

3.1.2.22 Restriction Type Rule - New

I Record Type: "Restriction Type Rule"

~~The record is used to create a restriction type rule.~~

~~Related activities covered:~~

TABLE 22 - ACT.18.2

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|------------------|--------------|---------------------------------------------|-------------------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| | | | | | | 1..1 | |
| | | | | | | | 1..1 |
| 3 | C | Restriction-Type | CHAR(4) | Restriction-type code. | | | |
| | | | | | | 1..1 | |
| | | | | | | | 1..1 |
| 4 | D | Sequence-Number | NUMERIC (9) | Sequence-number. | | | 1..1 |
| 5 | E | Valid-From | DATE | Valid-from-date of restriction-type rule. | Must be equal or greater than the current date. | | 1..1 |
| 6 | F | Valid-To | DATE | Valid-to-date of the restriction-type rule. | Must be greater than the Valid From-date. | | 0..1 |
| | | | | | | 0..10 | |
| 7 | G | Group | VARCHAR (35) | | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|------------------------------------------------------------------------------------------------------|-------------------|------------------|
| 8 | H | Restriction-Type Rule-Parameter Name | Name-of-the-parameter-type-to-be-set-for-the-rule: Allowed-values are: <ul style="list-style-type: none"> 'SMOV'-Seurities-Movement-Type 'PMNT'-Payment 'TRID'-Transaction-Identification 'AOPT'-Party-Type-(of-the-Account-Owner) 'OBPT'-Party-Type-(of-the-instr.-Party) 'PART'-Party | | Mandatory if Market-Specific Attribute-Name is not used. Not allowed otherwise. | | 0..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|-------|-------------------|------------------|
| | | | <ul style="list-style-type: none"> 'SECU'-Security Identifier 'CNIS'-Country of Issuance 'CRDB'-Credit Debit Indicator 'BLFR'-Balance From 'BLTO'-Balance To 'MTST'-Matching Status 'SACT'-Securities-Account 'SETC'-Settlement-Currency 'CACT'-T2S Dedicated-Cash Account 'CATP'-T2S Dedicated-Cash Account-Type | | | | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|---------------------------------------|--------------|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| 9 | I | Market-Specific Attribute-Name | VARCHAR (35) | Name of the market-specific attribute: | Mandatory if Restriction-Type-Rule Parameter-Name is not used. Not allowed otherwise. | | 0..1 |
| 10 | J | Restriction-Type Rule-Parameter Value | VARCHAR (35) | | Mandatory when Market-Specific Attribute-Name is specified or Restriction-Type-Rule Parameter-Name is: SMOV PMNT AOPT OBPT CNIS CRDB BLFR BLTO MTST | | 0..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|---------------------------------------------------|-----------------|-------------|----------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| | | | | | TRID SETC CATP Not allowed otherwise. | | |
| 11 | K | Party-Parent-BIC Parameter-Value | CHAR(11) | | Mandatory when Restriction-Type Rule-Parameter Name-is: PART Not allowed otherwise. | | 0..1 |
| 12 | L | Party-BIC-Para- meter-Value | CHAR(11) | | Mandatory when Restriction-Type Rule-Parameter Name-is: PART Not allowed otherwise. | | 0..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|----------------------------------------|-------------|-------------|--------------------------------------------------------------------------------------------------------|-------------------|------------------|
| 13 | M | Securities-Parameter-Value | CHAR(12) | | Mandatory when Restriction-Type Rule-Parameter Name-is: SECU Not allowed otherwise. | | 0..1 |
| 14 | N | Securities-Account-Parameter-Value | VARCHAR(35) | | Mandatory when Restriction-Type Rule-Parameter Name-is: SACT Not allowed otherwise. | | 0..1 |
| 15 | O | Dedicated-Cash-Account-Parameter-Value | VARCHAR(34) | | Mandatory when Restriction-Type Rule-Parameter Name-is: CACT Not allowed otherwise. | | 0..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|---------|-------------------------------------------------------------------------------|--------------------------------------------------------|-------------------|------------------|
| 16 | P | Debit | BOOLEAN | Specifies if the rule applies on the debit leg of the settlement instruction | Include-only-if Market-Specific Attribute-Name is used | | 0..1 |
| 17 | Q | Credit | BOOLEAN | Specifies if the rule applies on the credit leg of the settlement instruction | Include-only-if Market-Specific Attribute-Name is used | | 0..1 |

{CR-863}

~~3.1.2.23 Conditional Securities Delivery Rule Set – New~~

~~I Record Type: “CoSD Rule Set”~~

~~The record is used to create a conditional securities delivery rule set.~~

~~Related activities covered:~~

TABLE 23 - ACT-20.1

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|--------------|----------------------------------|----------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| | | | | | | 1..1 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|--------------------------|---------------|------------------------------------------------------------------|-------------------------------------------------|-------------------|------------------|
| 3 | C | Name | VARCHAR-(35) | Name of the conditional securities delivery rule set. | | | 1..1 |
| 4 | D | Description | VARCHAR-(350) | Description of the conditional securities delivery rule set. | | | 1..1 |
| 5 | E | Administering Parent-BIC | CHAR-(11) | BIC of the parent of the administering party. | | | 1..1 |
| 6 | F | Administering Party-BIC | CHAR-(11) | BIC of the administering party | | | 1..1 |
| 7 | G | Valid-From | DATE | Valid-from-date of the conditional securities delivery rule set. | Must be equal or greater than the current date. | | 1..1 |
| 8 | H | Valid-To | DATE | Valid-to-date of the conditional securities delivery rule set. | Must be greater than the Valid-From-date. | | 0..1 |
| 9 | I | Block-on-Cash-Side | BOOLEAN | I true = T2S shall block cash when an | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|--------------------------|---------|--------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| | | | | instruction is marked for conditional delivery | | | |
| 10 | 3 | Block-on-Securities Side | BOOLEAN | I true = T2S shall block securities when an instruction is marked for conditional delivery | | 1..1 | |

{CR-863}

3.1.2.24 Conditional Securities Delivery Rule - New

I Record Type: "CoSD Rule"

The record is used to create a conditional securities delivery rule.

Related activities covered:

TABLE 24 - ACT-20.2

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|--------------------------------------------------|--------------|-------------|--------------|----------------------------------|----------------------------------------|-------------------|------------------|
| 2 | 8 | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| Group "Conditional Securities Delivery Rule Set" | | | | | | 1..1 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|----------------------------------------------------------------|--------------|-------------------------------------------------------------------------------------------|-------------------------------------------------|-------------------|------------------|
| 3 | C | CeSD-Rule-Set Name | VARCHAR-(35) | Name of the conditional securities delivery rule set. | | | 1..1 |
| | | Group "Conditional Securities Delivery Rule" | | | | 1..1 | |
| 4 | D | Sequence-Number | NUMERIC-(9) | Sequence related to the rule. | | | 1..1 |
| 5 | E | Valid-From | DATE | Valid from date of the conditional securities delivery rule. | Must be equal or greater than the current date. | | 1..1 |
| 6 | F | Valid-To | DATE | Valid to date of the conditional securities delivery rule. | Must be greater than the Valid From date. | | 0..1 |
| 7 | G | CeSD-Processing | BOOLEAN | I true = The settlement instruction that matches with the rule is to settle conditionally | | | 1..1 |
| | | Group "Conditional Securities Delivery Rule Parameters" | | | | 1..10 | |
| 8 | H | Group | VARCHAR-(35) | | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|-------|-------------------|------------------|
| 9 | I | Conditional-Securities-Delivery-Rule-Parameter-Name | Name-of-the-parameter-type-to-be-set-for-the-rule: Allowed-values-are: <ul style="list-style-type: none"> ISIN STCR-(Settlement-Currency) CSD SACC-(Securities-Account) COIS-(Country-of-Issuance) PLSE-(Place-of-Settlement) ISSU-(Issuer-CSD-in-T2S) DELI-(Delivering-CSD-in-T2S) RECE-(Receiving-CSD-in-T2S) | | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|-------|-------------------|------------------|
| | | | <ul style="list-style-type: none"> ■ IBIC (BIC of Issuer-CSD in T2S) ■ DBIC (BIC of Delivering-CSD in T2S) ■ RBIC (BIC of Receiving-CSD in T2S) ■ TRCD (ISO transaction code) ■ SMTP (Securities-movement type) ■ PTPC (Payment type-code) ■ CDND (Credit Debit-indicator) | | | | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------------------------------------------------------|-------------------------------------------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| | | | ■ STCC (Settlement-transaction-condition-code) | | | | |
| 10 | 3 | Conditional-Securities-Delivery-Rule Parameter-Value | VARCHAR (35) | | Mandatory when Conditional-Securities-Delivery-Rule Parameter-Name is: STCR COIS TRCD SMTP PTPC CDND STCC Not allowed otherwise. | 0..1 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|------------------------------------|----------|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| 11 | K | Parameter-parent BIC-Identifier | CHAR(11) | | Mandatory when Conditional-Secur- ties-Delivery-Rule Parameter-Name is: CSD PLSE Not allowed other- wise. | | 0..1 |
| 12 | L | Parameter-Party BIC-Identifier | CHAR(11) | | Mandatory when Conditional-Secur- ties-Delivery-Rule Parameter-Name is: CSD PLSE IBIC DBIC RBIC Not allowed other- wise. | | 0..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-----------------------------------------|-------------|-------------|-----------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| 13 | M | Parameter-Securities-Identifier | CHAR(12) | | Mandatory when Conditional-Securities-Delivery-Rule Parameter-Name is: ISIN Not allowed otherwise. | | 0..1 |
| 14 | N | Parameter-Securities-Account-Identifier | VARCHAR(35) | | Mandatory when Conditional-Securities-Delivery-Rule Parameter-Name is: SACC Not allowed otherwise. | | 0..1 |
| 15 | O | Parameter-CSD-Flag-Value | BOOLEAN | | Mandatory when Conditional-Securities-Delivery-Rule Parameter-Name is: ISSU DELI | | 0..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|--------|-------------|--------------------------------------------------|-------------------|------------------|
| | | | | | RECE Not allowed otherwise. | | |

{CR-863}

3.1.2.25 Report Configuration—New

I Record Type: “Report Configuration”

The record is used to create a report configuration.

Related activities covered:

TABLE 25 - ACT.21.1

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------------------------------|------------------|----------------------------------|----------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| | | Group “Report Configuration” | | | | 1..1 | |
| 3 | C | Configuration Name | VARCHAR (35) | | | | 1..1 |
| 4 | D | Configuration Description | VARCHAR (350) | | | | 1..1 |
| 5 | E | Delta Mode | BOOLEAN | | | | 1..1 |
| 6 | F | Report Name | Possible values: | Name of the report type. | | | 1..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|-------|-------------------|------------------|
| | | | <ul style="list-style-type: none"> Statement-of Holdings Statement-of Transactions Statement-of Pending Instructions Statement-of Settlement Allegements Statement-of Accounts SD-T2S-DCA Statement SD-Securities AccountsStatement SD-Securities Statement SD-Party-Statement | | | | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|-------|-------------------|------------------|
| | | | <ul style="list-style-type: none"> Current-Busi-ness-Day-Cash-Forecast Next-Business-Day-Cash-Forecast Executed-AI-on-Cash Executed-AI-on-Securities Executed-CI-on-Cash Executed-CI-on-Securities Pending-AI-on-Cash Pending-AI-on-Securities Pending-CI-on-Cash Pending-CI-on-Securities | | | | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------------------------------------|--------------|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|-------|-------------------|------------------|
| | | | <ul style="list-style-type: none"> ■ Pending Restrictions on Cash ■ Pending Restrictions on Securities ■ Settled Restrictions on Cash ■ Settled Restrictions on Securities | | | | |
| 7 | G | System-Entity Wide-Reporting Flag | BOOLEAN | <ul style="list-style-type: none"> ■ true = System entity-wide reporting | | 1..1 | |
| Group "Report Configuration Party Link" | | | | | | 0..10 | |
| 8 | H | Parent-BIC | CHAR (11) | Parent-BIC of the linked-party. | | 1..1 | |
| 9 | I | Party-BIC | CHAR (11) | Party-BIC of the linked-party. | | 1..1 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|----------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|-------------------|------------------|
| 10 | 3 | Push-Mode | BOOLEAN | <ul style="list-style-type: none"> true = The recipient gets the report in push-mode false = The recipient gets the report in pull-mode | | | 1..1 |
| 11 | K | Execution-Time | TIME | Time of the execution of the report. | Mandatory if Event Type is not specified. Not allowed otherwise. | | 0..1 |
| 12 | L | Event-Type | CHAR (4) | Code of the event type that triggers the report. | Mandatory if Execution-Time is not specified. Not allowed otherwise. | | 0..1 |
| 13 | M | Valid-From | DATE | Starting date for the validity period. | Must be greater than the current date. | | 1..1 |
| 14 | N | Valid-To | DATE | Ending date for the validity period. | Must be equal or greater than the Valid-From date. | | 0..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|---------|---------------------------------------------|-------|-------------------|------------------|
| 15 | E | Currency | CHAR(3) | Currency-linked to the Report Configuration | | | 0..1 |

{CR-863}

3.1.2.26 Eligible Counterpart CSD - New

I Record Type: "Eligible Counterpart CSD"

The record is used to create an eligible counterpart CSD.

Related activities covered:

TABLE 26 - ACT.22.1

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|-------------|----------------------------------|-------------------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC(10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| 3 | C | Valid-From | DATE | Valid-from-date. | Must be equal or greater than the current date. | | 1..1 |
| 4 | D | Valid-To | DATE | Valid-to-date. | Must be greater than the Valid From date. | | 0..1 |
| Group "Investor" | | | | | | 1..1 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|-----------------------------------------|--------------|--------------------------------------|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------|------------------|
| 5 | E | Investor-Parent BIC | CHAR-(11) | Parent BIC of the investor. | | | 1..1 |
| 6 | F | Investor-BIC | CHAR-(11) | | | | 1..1 |
| Group "Eligible-Counterpart-CSD" | | | | | | 1..1 | |
| 7 | G | Eligible-counter-part-CSD-Parent BIC | CHAR-(11) | Parent BIC of the eligible-counter-part-CSD. | | | 1..1 |
| 8 | H | Eligible-counter-part-CSD-BIC | CHAR-(11) | | | | 1..1 |
| Group "Eligibility-Type" | | | | | | 1..1 | |
| 9 | I | Eligibility-Type | Possible-values: | Possible-values: <ul style="list-style-type: none">■ SECU■ CTRY■ ISCS <ul style="list-style-type: none">■ SECU = Securities■ CTRY = Country■ ISCS = Issuer CSD | | | 1..1 |
| 10 | J | ISIN | CHAR-(12) | Security-identification. | Must occur if Eligibility-Type is 'Securities'. Otherwise the cell must be empty. | | 0..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------------|-----------|------------------|-----------------------------------------------------------------------------------|-------------------|------------------|
| 11 | K | Country-code | CHAR-(2) | | Must occur if Eligibility-Type is 'Country'. Otherwise the cell must be empty. | | 0..1 |
| 12 | L | Issuer-Parent-BIC | CHAR-(11) | External-issuer. | Must occur if Eligibility-Type is 'Issuer-CSD'. Otherwise the cell must be empty. | | 0..1 |
| 13 | M | Issuer-BIC | CHAR-(11) | | | | |

{CR-863}

3.1.2.27 Certificate Distinguished Name

I Record Type: "Certificate-DN"

The record is used to create a certificate-distinguished-name.

TABLE 27 - ACT.16.5

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|-------------|--------------|----------------------------------|-------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC-(10) | Unique identifier of the record. | | 1..1 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|--------------------------------|---------------|-------------|--------------------------------------------------------------------|-------------------|------------------|
| 3 | C | Certificate-Distinguished-Name | VARCHAR-(256) | | ISO15022-interoperability-character-set-restriction-does-not-apply | 1..1 | |

{CR-863}

3.1.2.28 User Certificate Distinguished Name Link

I Record Type: "User Certificate DN Link"

The record is used to create a link between a Certificate DN and a T2S System User.

TABLE 28 - ACT-16.6

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|--------------------------------|---------------|----------------------------------|--------------------------------------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC-(10) | Unique identifier of the record. | | 1..1 | |
| 3 | C | Certificate-Distinguished-Name | VARCHAR-(256) | | ISO15022-interoperability-character-set-restriction-does-not-apply | 1..1 | |
| 4 | D | Login-Name | VARCHAR-(35) | T2S-User's login name. | | 1..1 | |
| 5 | E | Default | BOOLEAN | | | 1..1 | |

{CR-863}

3.1.2.29 Restrictions on Securities Account—New

| Flat File Column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|-----------------------------------------------|--------------|-----------------------------|--------------|----------------------------------------------|-------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| 2 | B | Record Id | NUMERIC (10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| Group "Securities Account" | | | | | | 1..1 | |
| 3 | C | Securities Account Number | VARCHAR (35) | Unique securities account number. | | | 1..1 |
| Group "Securities Account Restriction" | | | | | | 1..10 | |
| 4 | D | Restriction Type | CHAR (4) | Code of the restriction to be applied. | | | 1..1 |
| 5 | E | Restriction Valid From Date | DATE | Valid from date and time of the restriction. | It is optional in case of immediate removal of restrictions. | | 0..1 |
| 6 | G | Restriction Valid From Time | TIME | | Must be equal to or greater than the current date and time, except for the immediate setup of restrictions. | | 0..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|---------------------------|--------|--------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| | | | | | In this case the value is "1000-01-01 00:01:00". | | |
| 7 | G | Restriction-Valid To-Date | DATE | Valid to date and time of the restriction: | Must be equal to or greater than the valid from date and time, except for the immediate removal of restrictions. In this case the value is "9999-12-31 23:59:00". | 0..1 | |
| 8 | H | Restriction-Valid To-Time | TIME | | | 0..1 | |

{CR-863}

3.1.2.30 Restrictions on T2S Dedicated Cash Accounts—New

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|-------------------------------------------|--------------|-------------|-------------|----------------------------------|----------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC(10) | Unique identifier of the record. | Must occur in each line of the record. | 1..n | |
| Group "T2S Dedicated Cash Account" | | | | | | 1..1 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|-------------------------------------------------------|--------------|-----------------------------------|--------------|----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| 3 | C | T2S-Dedicated-Cash-Account-Number | VARCHAR-(34) | Unique T2S-Dedicated-Cash-Account number. | | | 1..1 |
| Group "T2S-Dedicated-Cash-Account-Restriction" | | | | | | | |
| 4 | D | Restriction-Type | CHAR-(4) | Code of the restriction to be applied. | | | 1..1 |
| 5 | E | Restriction-Valid-From-Date | DATE | Valid from date and time of the restriction. | It is optional in case of immediate removal of restrictions. | | 0..1 |
| 6 | G | Restriction-Valid-From-Time | TIME | | Must be equal to or greater than the current date and time, except for the immediate setup of restrictions. In this case the value is "1000-01-01 00:01:00". | | 0..1 |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|---------------------------|--------|--------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| 7 | G | Restriction-Valid To-Date | DATE | Valid-to-date-and time-of-the-restriction: | Must-be-equal-to or-greater-than-the valid-from-date and-time, except for-the-immediate removal-of-restrictions. In this case the-value-is "9999-12-31 23:59:00". | | 0..1 |
| 8 | H | Restriction-Valid To-Time | TIME | | | | 0..1 |

{CR-863}

3.1.2.31 Euro Foreign Exchange Reference Rate—New

I Record Type: "Euro Foreign Exchange Reference Rate"

This record is used to create a Euro Foreign Exchange Reference Rate used to perform the daily computation of cash penalties.

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs per-Record | Occurs per-Group |
|------------------|--------------|----------------------------------------------|-------------|------------------------------------------|----------------------------------------|-------------------|------------------|
| 2 | B | Record-Id | NUMERIC(10) | Unique-identifier of-the-record. | Must-occur-in-each line-of-the-record. | 1..1 | |
| | | Group "Euro Foreign Exchange Reference Rate" | | | | 1..1 | |
| 3 | C | Currency-Code | CHAR(3) | Currency-for-which the-rate-is provided. | | 1..1 | |

| Flat-file-column | Excel-Column | Column-Name | Format | Description | Rules | Occurs-per-Record | Occurs-per-Group |
|------------------|--------------|---------------------|-----------|-------------------------------------|-------|-------------------|------------------|
| 4 | D | Daily Exchange Rate | DEC(14,5) | Actual rate. | | | 1..1 |
| 5 | E | Exchange Rate Date | DATE | Date for which the rate is provided | | | 1..1 |

{CR-863}

3.1.3 Dynamic Data

3.1.3.1 Free of Payment Settlement Instruction

■ Record Type: "FOP"

The record is used to create a free of payment settlement instruction.

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record |
|------------------|--------------|---------------------------------|---------------------------------------------------|----------------------------------|-------|-------------------|
| 2 | B | Record Id | NUMERIC (10) | Unique identifier of the record. | | 1..1 |
| 3 | C | Instructing Party Parent BIC | VARCHAR (11) | | | 1..1 |
| 4 | D | Instructing Party BIC | VARCHAR (11) | | | 1..1 |
| 5 | E | T2S Actor Instruction Reference | VARCHAR (16) RestrictedFIN- Max16Text_T2S_1 | Transaction identification. | | 1..1 |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record |
|------------------|--------------|-------------------------------|---------------------------------------------------|------------------------------------------------------------------------|------------------------------------------------------------|-------------------|
| 6 | F | Securities Movement Type Code | Possible values: ■ DELI ■ RECE | ■ DELI = Delivery ■ RECE = Receive | | 1..1 |
| 7 | G | Payment Type Code | Possible value: ■ FREE | ■ FREE = FoP instruction | | 1..1 |
| 8 | H | Trade Date | DATE | | Must be equal or earlier than the Intended Settlement Date | 1..1 |
| 9 | I | Intended Settlement Date | DATE | Go-live date | | 1..1 |
| 10 | J | Already matched instruction | Possible values: ■ MACH ■ NMAT | ■ MACH = Already matched instruction ■ NMAT = Unmatched instruction | | 1..1 |
| 11 | K | Common Reference | VARCHAR (16) RestrictedFIN- Max16Text_T2S_1 | | | 1..1 |
| 12 | L | ISIN | CHAR(12) | | | 1..1 |
| 13 | M | Settlement Type | Possible values: ■ UNIT ■ FAMT | Type of quantity: ■ UNIT = Unit | | 1..1 |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record |
|------------------|--------------|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|
| | | | | <ul style="list-style-type: none"> ■ FAMT = Face Amount | | |
| 14 | N | Settlement Quantity | DEC (14,14)* when Settlement Type is 'UNIT' DEC (14,5)* when Settlement Type is 'FAMT' | | | 1..1 |
| 15 | O | Securities Account Number | VARCHAR (35) | Safekeeping account. | | 1..1 |
| 16 | P | ISO Transaction Code | Possible values: <ul style="list-style-type: none"> ■ AUTO ■ BSBK ■ BYIY ■ CLAI ■ CNCB ■ COLI ■ COLO ■ CONV ■ CORP ■ ETFT ■ FCTA | Securities transaction type: <ul style="list-style-type: none"> ■ AUTO = Auto Collateralisation ■ BYIY = BuyIn ■ BSBK = Buy Sell Back ■ CLAI = Market Claim ■ CNCB = Central Bank Collateral Operation ■ COLI = Collateral In ■ COLO = Collateral Out | | 1..1 |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record |
|------------------|--------------|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|
| | | | <ul style="list-style-type: none"> ■ INSP ■ ISSU ■ MKDW ■ MKUP ■ NETT ■ NSYN ■ OWNE ■ OWNI ■ PAIR ■ PLAC ■ PORT ■ REAL ■ REDI ■ REDM ■ RELE ■ REPU ■ RODE ■ RVPO ■ SBBK | <ul style="list-style-type: none"> ■ CONV = Depository Receipt Conversion ■ CORP = Corporate Action ■ ETFT = Exchange Traded Funds ■ FCTA = Factor Update ■ INSP = Move of Stock ■ ISSU = Issuance ■ MKDW = Mark Down ■ MKUP = Mark Up ■ NETT = Netting ■ NSYN = Non Syndicated ■ OWNE = External Account Transfer ■ OWNI = Internal Account Transfer | | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record |
|------------------|--------------|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|
| | | | <ul style="list-style-type: none"> ■ SBRE ■ SECB ■ SECL ■ SLRE ■ SUBS ■ SWIF ■ SWIT ■ SYND ■ TBAC ■ TRAD ■ TRPO ■ TRVO ■ TURN | <ul style="list-style-type: none"> ■ PAIR = Pair Off ■ PLAC = Placement ■ PORT = Portfolio Move ■ REAL = Realignment ■ REDI = Withdrawal ■ REDM = Redemption ■ RELE = Depository Receipt Release ■ CANCELLATION = Cancellation ■ REPU = Repo ■ RODE = Return Delivery without Matching ■ RVPO = Reverse Repurchase Agreement ■ SBBK = Sell Buy Back ■ SBRE = Borrowing Reallocation | | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record |
|------------------|--------------|--------------------------|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|-------------------|
| | | | | <ul style="list-style-type: none"> ■ SECB = Securities Borrowing ■ SECL = Securities Lending ■ SLRE = Lending Reallocation ■ SUBS = Subscription ■ SWIF = Switch From ■ SWIT = Switch To ■ SYND = Syndicate Underwriters ■ TBAC = TBA Closing ■ TRAD = Trade ■ TRPO = Triparty Repo ■ TRVO = Triparty Reverse Repo ■ TURN = Turnaround | | |
| 17 | Q | Receiving Depository BIC | VARCHAR (11) | | Must occur when Securities Movement Type Code is 'DELI'. | 0..1 |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record |
|------------------|--------------|-------------------------------------------|--------------|-------------------------------|---------------------------------------------------------------------------------------------------------|-------------------|
| 18 | R | T2S Receiving Party BIC | VARCHAR (11) | | Must occur when Securities Movement Type Code is 'DELI'. | 0..1 |
| 19 | S | T2S Receiving Party Securities Account | VARCHAR (35) | | Must occur when when Securities Movement Type Code is 'DELI' and Already matched instruction is 'MACH'. | 0..1 |
| 20 | T | Delivering Depository BIC | VARCHAR (11) | | Must occur when Securities Movement Type Code is 'RECE'. | 0..1 |
| 21 | U | T2S Delivering Party BIC | VARCHAR (11) | | Must occur when Securities Movement Type Code is 'RECE'. | 0..1 |
| 22 | V | T2S Delivering Party Securities Account | VARCHAR (35) | | Must occur when Securities Movement Type Code is 'RECE' and Already matched instruction is 'MACH'. | 0..1 |
| 23 | W | Delivering Securities Sub-Balance Type Id | CHAR(4) | Set up an earmarked position. | Can only be filled in if Securities Movement Type Code is 'DELI' or if | 0..1 |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record |
|------------------|--------------|----------------------------------------------------|--------------------------|-------------------------------|-------------------------------------------------------------------------------------------------------------------|-------------------|
| | | | | | the settlement instruction is sent already matched | |
| 24 | X | Delivering Securities Sub-Balance Type Issuer | Possible value: ■ T2S | | Must be present if Delivering Securities Sub-Balance Type Id is present. | 0..1 |
| 25 | Y | Delivering Securities Sub-Balance Type Scheme Name | Possible value: ■ RT | RT = Restriction Type | Must be present if Delivering Securities Sub-Balance Type Id is present. | 0..1 |
| 26 | Z | Receiving Securities Sub-Balance Type Id | CHAR(4) | Set up an earmarked position. | Can only be filled in if Securities Movement Type Code is 'RECE' or if the instruction is sent as already matched | 0..1 |
| 27 | AA | Receiving Securities Sub-Balance Type Issuer | Possible value: ■ T2S | | Must be present if Receiving Securities Sub-Balance Type Id is present. | 0..1 |
| 28 | AB | Receiving Securities Sub-Balance Type Scheme Name | Possible value: ■ RT | RT = Restriction Type | Must be present if Receiving Securities Sub-Balance Type Id is present | 0..1 |

RestrictedFINMax16Text_T2S_1 :

Pattern: [0-9a-zA-Z|-|?:|(||.|'|+|/|?|[0-9a-zA-Z|-|?:|(||.|'|+|/|?)*|[0-9a-zA-Z|-|?:|(||.|'|+|+|)?

3.1.3.2 Settlement Restriction

Record Type: "Settlement Restriction"

The record is used to create a settlement restriction.

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|---------------------------------|----------------------------------------------------|-----------------------------------------------------------------------------------|-------|-------------------|------------------|
| 2 | B | Record Id | NUMERIC (10) | Unique identifier of the record. | | 1..1 | |
| 3 | C | Instructing Party Parent BIC | VARCHAR (11) | | | 1..1 | |
| 4 | D | Instructing Party BIC | VARCHAR (11) | | | 1..1 | |
| 5 | E | T2S Actor Instruction Reference | VARCHAR (16) – RestrictedFIN- Max16Text_T2S_1 | Transaction identification. | | 1..1 | |
| 6 | F | Intended Settlement Date | DATE | | | 1..1 | |
| 7 | G | Priority | Possible values: ■ 0001 ■ 0003 ■ 0004 | Values for priority: ■ 0001 = Reserved ■ 0003 = High ■ 0004 = Normal | | 0..1 | |
| 8 | H | Securities Account Number | VARCHAR (35) | | | 1..1 | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|---------------------------|-----------------------------------------------------------------------------------------------|--------------------------------------------------------------------|-------|-------------------|------------------|
| 9 | I | ISIN | CHAR(12) | | | 1..1 | |
| 10 | J | Settlement Type | Possible values: ■ UNIT ■ FAMT | Type of quantity: ■ UNIT = Unit ■ FAMT = Face Amount | | 1..1 | |
| 11 | K | Settlement Quantity | DEC (14,14)* when Settlement Type is 'UNIT' DEC (14,5)* when Settlement Type is 'FAMT' | | | 1..1 | |
| 12 | L | Corporate Action Event id | VARCHAR(16) – RestrictedFIN- Max16Text_T2S_1 | | | 0..1 | |
| 13 | M | Balance From | CHAR(4) | AWAS to indicate movement FROM "Deliverable" position | | 1..1 | |
| 14 | N | Balance To | CHAR(4) | AWAS to indicate movement TO "Deliverable" position | | 1..1 | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|-------------------|------------------|
| 15 | O | Restriction Reference Id | VARCHAR(30) | Restriction Reference as assigned by T2S during the setup of a restriction | | 0..1 | |
| 16 | P | Link Instruction Counter | NUMERIC(3) | Number of instructions that are included in the pool, if the instruction belongs to a pool. | Mandatory if the instruction belongs to a pool. | 0..1 | |
| Group "Linkage" | | | | | | 0..100 | |
| 17 | Q | Link Processing Position | Possible values: <ul style="list-style-type: none">■ AFTE■ BEFO■ INFO■ WITH | Type of linkage | | | 0..1 |
| 18 | R | Securities Settlement Transaction id | VARCHAR (16) – RestrictedFIN- Max16Text_T2S_1 | Reference of the Settlement Instruction to be linked | Only one reference must be provided per occurrence of linkages block. | | 0..1 |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|--------------------------------------|-----------------------------------------------|-----------------------------------------------------------------|-----------------------------------------------------------------------|-------------------|------------------|
| 19 | S | Intra Position Movement Id | VARCHAR (16) – RestrictedFIN- Max16Text_T2S_1 | Reference of the Securities Settlement Restriction to be linked | Only one reference must be provided per occurrence of linkages block. | | 0..1 |
| 20 | T | Intra Balance Movement Id | VARCHAR (16) – RestrictedFIN- Max16Text_T2S_1 | Reference of the Cash Settlement Restriction to be linked | Only one reference must be provided per occurrence of linkages block. | | 0..1 |
| 21 | U | Account Servicer Transaction Id | VARCHAR (16) – RestrictedFIN- Max16Text_T2S_1 | Reference of the instructions provided by the Account Servicer | Only one reference must be provided per occurrence of linkages block. | | 0..1 |
| 22 | V | Market Infrastructure Transaction Id | VARCHAR (16) – RestrictedFIN- Max16Text_T2S_1 | T2S reference of the instruction to be linked | Only one reference must be provided per occurrence of linkages block. | | 0..1 |
| 23 | W | Pool Id | VARCHAR (16) – RestrictedFIN- Max16Text_T2S_1 | Pool Identification to be linked | Only one reference must be provided per occurrence of linkages block. | | 0..1 |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|----------------------|--------------------------------------------------|--------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| 24 | X | Other Transaction Id | VARCHAR (16) – RestrictedFIN- Max16Text_T2S_1 | Reference of the instruction provided by a Third Party | Only one reference must be provided per occurrence of linkages block. | | 0..1 |
| 25 | Y | Reference Owner BIC | VARCHAR (11) | BIC of the reference's owner | Must occur when one of the following fields is present: <ul style="list-style-type: none"> ■ Securities Settlement Transaction Id ■ IntraPosition-Movement Id ■ IntraBalanceMovement Id ■ AccountServicer Transaction Id ■ Pool Id ■ Other Transaction Id | | 0..1 |

RestrictedFINMax16Text_T2S_1 :

■ Pattern: [0-9a-zA-Z|-|?:|(|)|,|+]/(/?([0-9a-zA-Z|-|?:|(|)|,|+]/?)*)[0-9a-zA-Z|-|?:|(|)|,|+]+)?

3.1.3.3 Pending Instruction

■ Record Type: "Pending Instruction"

The record is used to create a pending instruction.

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|---------------------------------|---------------------------------------------------|------------------------------------------------------|-------|-------------------|------------------|
| 2 | B | Record Id | NUMERIC (10) | Unique identifier of the record. | | 1..1 | |
| 3 | C | Instructing Party Parent BIC | VARCHAR (11) | | | 1..1 | |
| 4 | D | Instructing Party BIC | VARCHAR (11) | | | 1..1 | |
| 5 | E | T2S Actor Instruction Reference | VARCHAR (16) RestrictedFIN- Max16Text_T2S_1 | Transaction identification. | | 1..1 | |
| 6 | F | Securities Movement Type Code | Possible values: ■ DELI ■ RECE | ■ DELI = Delivery ■ RECE = Receive | | 1..1 | |
| 7 | G | Payment Type Code | Possible value: ■ FREE ■ APMT | ■ FREE = FoP instruction ■ APMT = Against Payment | | 1..1 | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-----------------------------|---------------------------------------------------|------------------------------------------------------------------------|------------------------------------------------------------|-------------------|------------------|
| 8 | H | Trade Date | DATE | | Must be equal or earlier than the Intended Settlement Date | 1..1 | |
| 9 | I | Intended Settlement Date | DATE | | | 1..1 | |
| 10 | J | Already matched instruction | Possible values: ■ MACH ■ NMAT | ■ MACH = Already matched instruction ■ NMAT = Unmatched instruction | | 0..1 | |
| 11 | K | Common Reference | VARCHAR (16) RestrictedFIN- Max16Text_T2S_1 | | | 0..1 | |
| 12 | L | ISIN | CHAR(12) | | | 1..1 | |
| 13 | M | Settlement Type | Possible values: ■ UNIT ■ FAMT | Type of quantity: ■ UNIT = Unit ■ FAMT = Face Amount | | 1..1 | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| 14 | N | Settlement Quantity | DEC (14,14)* when Settlement Type is 'UNIT' DEC (14,5)* when Settlement Type is 'FAMT' | | | 1..1 | |
| 15 | O | Securities Account Number | VARCHAR (35) | Safekeeping account. | | 1..1 | |
| 16 | P | ISO Transaction Code | Possible values: ■ AUTO ■ BSBK ■ BYIY ■ CLAI ■ CNCB ■ COLI ■ COLO ■ CONV ■ CORP ■ FCTA ■ INSP | Securities transaction type: ■ AUTO = Auto Collateralisation ■ BSBK = Buy Sell Back ■ BYIY = BuyIn ■ CLAI = Market Claim ■ CNCB = Central Bank Collateral Operation ■ COLI = Collateral In | | 1..1 | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| | | | <ul style="list-style-type: none"> ■ ISSU ■ MKDW ■ MKUP ■ NETT ■ NSYN ■ OWNE ■ OWNI ■ PAIR ■ PLAC ■ PORT ■ REAL ■ REDI ■ REDM ■ RELE ■ REPU ■ RODE ■ RPTO ■ RVPO ■ SBBK | <ul style="list-style-type: none"> ■ COLO = Collateral Out ■ CONV = Depository Receipt Conversion ■ CORP = Corporate Action ■ FCTA = Factor Update ■ INSP = Move of Stock ■ ISSU = Issuance ■ MKDW = Mark Down ■ MKUP = Mark Up ■ NETT = Netting ■ NSYN = Non Syndicated ■ OWNE = External Account Transfer ■ OWNI = Internal Account Transfer | | | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| | | | <ul style="list-style-type: none"> ■ SBRE ■ SECB ■ SECL ■ SLRE ■ SUBS ■ SWIF ■ SWIT ■ SYND ■ TBAC ■ TRAD ■ TRPO ■ TRVO ■ TURN | <ul style="list-style-type: none"> ■ PAIR = Pair Off ■ PLAC = Place- ment ■ PORT = Portfolio Move ■ REAL = Realign- ment ■ REDI = With- drawal ■ REDM = Re- demption ■ RELE = Deposit- ory Receipt Re- lease Cancella- tion ■ REPU = Repo ■ RODE = Return Delivery without Matching ■ RPTO = Report- ing | | | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-------------|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| | | | | <ul style="list-style-type: none"> ■ RVPO = Reverse Repurchase Agreement ■ SBBK = Sell Buy Back ■ SBRE = Borrowing Reallocation ■ SECB = Securities Borrowing ■ SECL = Securities Lending ■ SLRE = Lending Reallocation ■ SUBS = Subscription ■ SWIF = Switch From ■ SWIT = Switch To ■ SYND = Syndicate Underwriters | | | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|--------------------------|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| | | | | <ul style="list-style-type: none"> ■ TBAC = TBA Closing ■ TRAD = Trade ■ TRPO = Triparty Repo ■ TRVO = Triparty Reverse Repo ■ TURN = Turn-around | | | |
| 17 | Q | Receiving Depository BIC | VARCHAR (11) | | <p>Must occur when Securities Movement Type Code is 'DELI'.</p> <p>Must occur when T2S Receiving Party BIC is included</p> | 0..1 | |
| 18 | R | T2S Receiving Party BIC | VARCHAR (11) | | <p>Must occur when Securities Movement Type Code is 'DELI'.</p> <p>Must be present if Receiving CSD Participant's Client BIC is present.</p> | 0..1 | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-----------------------------------------|--------------|-------------|------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| 19 | S | T2S Receiving Party Securities Account | VARCHAR (35) | | Must occur when Securities Movement Type Code is 'DELI' and Already matched instruction is 'MACH'. | 0..1 | |
| 20 | T | Delivering Depository BIC | VARCHAR (11) | | Must occur when Securities Movement Type Code is 'RECE'. Must occur when T2S Delivering Party BIC is included | 0..1 | |
| 21 | U | T2S Delivering Party BIC | VARCHAR (11) | | Must occur when Securities Movement Type Code is 'RECE'. Must be present if Delivering CSD Participant's Client BIC is present. | 0..1 | |
| 22 | V | T2S Delivering Party Securities Account | VARCHAR (35) | | Must occur when Securities Movement Type Code is 'RECE' and Already matched instruction is 'MACH'. | 0..1 | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|----------------------------------------------------|--------------------------|-------------------------------|------------------------------------------------------------------------------------------------|-------------------|------------------|
| 23 | W | Delivering Securities Sub-Balance Type Id | CHAR(4) | Set up an earmarked position. | Can only be filled in if Securities Movement Type Code is 'DELI' or it is sent already matched | 0..1 | |
| 24 | X | Delivering Securities Sub-Balance Type Issuer | Possible value: ■ T2S | | Must be present if Delivering Securities Sub-Balance Type Id is present. | 0..1 | |
| 25 | Y | Delivering Securities Sub-Balance Type Scheme Name | Possible value: ■ RT | RT = Restriction Type | Must be present if Delivering Securities Sub-Balance Type Id is present. | 0..1 | |
| 26 | Z | Receiving Securities Sub-Balance Type Id | CHAR(4) | Set up an earmarked position. | Can only be filled in if Securities Movement Type Code is 'RECE' or it is sent already matched | 0..1 | |
| 27 | AA | Receiving Securities Sub-Balance Type Issuer | Possible value: T2S | | Must be present if Receiving Securities Sub-Balance Type Id is present. | 0..1 | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|---------------------------------------------------------|-------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| 28 | AB | Receiving Securities Sub-Balance Type Scheme Name | Possible value: RT | RT = Restriction Type | Must be present if Receiving Securities Sub-Balance Type Id is present. | 0..1 | |
| 29 | AC | Corporate Action Event id | VARCHAR(16) – RestrictedFIN- Max16Text_T2S_1 | For migrating pending instructions with ISD in the past, this field has to be filled in with the special migration code-word. | | 0..1 | |
| 30 | AD | Cash Account | VARCHAR(34) | | Must be present if "Debtor Dedicated Cash Account Number" is present and Credit/Debit Indicator is 'DBIT' Must be present if "Creditor Dedicated Cash Account Number" is present and Credit/Debit Indicator is 'CRDT' | 0..1 | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|----------------|------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| 31 | AE | Hold Indicator | <p>BOOLEAN</p> <p>Possible values:</p> <ul style="list-style-type: none"> ■ true ■ false | <p>Possible values:</p> <ul style="list-style-type: none"> ■ 'true': For unmatched instructions, the instruction is set on hold For already matched instructions, at least one of the legs of the transaction is set on hold depending on the Hold Status Type. ■ 'false': For unmatched instructions, no hold applies in settlement instruction. For already matched instructions, no hold applies in any leg of the transaction. | <ul style="list-style-type: none"> ■ If the hold indicator is set to true, at least one occurrence of Hold Status Type must be present. ■ If the hold indicator is set to false or empty, the Hold Status Types column must not be present. | 0..1 | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-------------------|---------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| | | | | <ul style="list-style-type: none"> ■ If not specified, SAC's default value is applied. | | | |
| 32 | AF | Priority | Possible values: <ul style="list-style-type: none"> ■ 0001 ■ 0003 ■ 0004 | Values for priority: <ul style="list-style-type: none"> ■ 0001 = Reserved ■ 0003 = High ■ 0004 = Normal | | 0..1 | |
| 33 | AG | Partial Indicator | Possible values: <ul style="list-style-type: none"> ■ NPAR ■ PARC ■ PARQ ■ PART | Threshold type and type of partial settlement: <ul style="list-style-type: none"> ■ NPAR = Partial-NotAllowed ■ PARC = Partial-SettlementCash-ThresholdAllowed ■ PARQ = Partial-Settle-mentQuantity-ThresholdAllowed ■ PART = PartialAllowed | | 0..1 | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-----------------------------------|---------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| 34 | AH | Modification/Cancellation allowed | Possible values: TRUE FALSE BOTH NONE | Description of values : ■ TRUE = only the instructed leg can be modified / cancelled ■ FALSE = – In Already Matched SIs, the instructed leg cannot be modified / cancelled, but the T2S generated counter-leg can – In Unmatched SIs, the instructed leg cannot be modified / cancelled | ■ For an unmatched settlement instruction only the following codes for the Modification Cancellation Allowed are allowed: – TRUE – FALSE ■ If any value is specified: – In Already Matched SIs default value is BOTH – In Unmatched SIs default value is TRUE | 0..1 | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-----------------------------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|-------------------|------------------|
| | | | | <ul style="list-style-type: none"> ■ BOTH = both legs can be modified / cancelled ■ NONE = neither the instructed nor the T2S generated leg can be modified / cancelled | | | |
| 35 | AI | Delivering CSD Participant's Client BIC | VARCHAR(11) | | Must be present if Delivering Party 3 BIC is present | 0..1 | |
| 36 | AJ | Delivering Party 3 BIC | VARCHAR(11) | | Must be present if Delivering Party 4 BIC is present | 0..1 | |
| 37 | AK | Delivering Party 4 BIC | VARCHAR(11) | | | 0..1 | |
| 38 | AL | Receiving CSD Participant's Client BIC | VARCHAR(11) | | Must be present if Receiving Party 3 BIC is present | 0..1 | |
| 39 | AM | Receiving Party 3 BIC | VARCHAR(11) | | Must be present if Receiving Party 4 BIC is present | 0..1 | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|----------------------------------------|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| 40 | AN | Receiving Party 4 BIC | VARCHAR(11) | | | 0..1 | |
| 41 | AO | Debtor Party BIC | VARCHAR(11) | | | 0..1 | |
| 42 | AP | Debtor Dedicated Cash Account Number | VARCHAR(34) | | | 0..1 | |
| 43 | AQ | Creditor Party BIC | VARCHAR(11) | | | 0..1 | |
| 44 | AR | Creditor Dedicated Cash Account Number | VARCHAR(34) | | | 0..1 | |
| 45 | AS | Settlement Amount | DEC(14,5) | Must occur when Payment Type Code is 'APMT' <i>"For the triplet currency – credit/debit code - Settlement amount, all of them are optional for FOP instructions. However as soon as one of them is filled in, the other two become mandatory. (I.e. In case of payment</i> | | 0..1 | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-------------|---------|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| | | | | | <p><i>Type Code is 'FREE', the field 'Settlement Amount' is optional, but if it is filled in, the fields 'Currency' and 'Credit/Debit Indicator' must be informed too. Therefore, in case any of the three APMT related fields is filled in, the three of them must be filled in together)"</i></p> | | |
| 46 | AT | Currency | CHAR(3) | | <p>Must occur when Payment Type Code is 'APMT'</p> <p><i>"For the triplet currency – credit/debit code - Settlement amount, all of them are optional for FOP instructions. However as soon as one of</i></p> | 0..1 | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|------------------------|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| | | | | <p><i>them is filled in, the other two become mandatory. (I.e. In case of payment Type Code is 'FREE', the field 'Settlement Amount' is optional, but if it is filled in, the fields 'Currency' and 'Credit/Debit Indicator' must be informed too. Therefore, in case any of the three APMT related fields is filled in, the three of them must be filled in together)"</i></p> | | | |
| 47 | AU | Credit/Debit Indicator | Possible values: ■ CRDT ■ DBIT | Credit/Debit code: ■ CRDT = Credit ■ DBIT = Debit | Must occur when Payment Type Code is 'APMT' <i>"For the triplet currency – credit/debit code - Settlement</i> | 0..1 | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-------------|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| | | | | <i>amount, all of them are optional for FOP instructions. However as soon as one of them is filled in, the other two become mandatory. (I.e. In case of payment Type Code is 'FREE', the field 'Settlement Amount' is optional, but if it is filled in, the fields 'Currency' and 'Credit/Debit Indicator' must be informed too. Therefore, in case any of the three APMT related fields is filled in, the three of them must be filled in together)"</i> | | | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------|-----------------------------------------------------------------------|-------------------|------------------|
| 48 | AV | Link Instruction Counter | NUMERIC (3) | | Mandatory if the instruction belongs to a pool. | 0..1 | |
| Group "Linkage" | | | | | | 0..100 | |
| 49 | AW | Link Processing Position | Possible values: <ul style="list-style-type: none">■ AFTE■ BEFO■ INFO■ WITH | Type of linkage | | | 0..1 |
| 50 | AX | Securities Settlement Transaction id | VARCHAR (16) - RestrictedFIN- Max16Text_T2S_1 | Reference of the Settlement Instruction to be linked | Only one reference must be provided per occurrence of linkages block. | | 0..1 |
| 51 | AY | Intra Position Movement Id | VARCHAR (16) - RestrictedFIN- Max16Text_T2S_1 | Reference of the Securities Settlement Restriction to be linked | Only one reference must be provided per occurrence of linkages block. | | 0..1 |
| 52 | AZ | Intra Balance Movement Id | VARCHAR (16) - RestrictedFIN- Max16Text_T2S_1 | Reference of the Cash Settlement Restriction to be linked | | | 0..1 |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|--------------------------------------|-----------------------------------------------|----------------------------------------------------------------|---------------------------------------------------------------------------------------------------|-------------------|------------------|
| 53 | BA | Account Servicer Transaction Id | VARCHAR (16) – RestrictedFIN- Max16Text_T2S_1 | Reference of the instructions provided by the Account Servicer | Only one reference must be provided per occurrence of linkages block. | | 0..1 |
| 54 | BB | Market Infrastructure Transaction Id | VARCHAR (16) – RestrictedFIN- Max16Text_T2S_1 | T2S reference of the instruction to be linked | Only one reference must be provided per occurrence of linkages block. | | 0..1 |
| 55 | BC | Pool Id | VARCHAR (16) – RestrictedFIN- Max16Text_T2S_1 | Pool Identification to be linked | Only one reference must be provided per occurrence of linkages block. | | 0..1 |
| 56 | BD | Other Transaction Id | VARCHAR (16) – RestrictedFIN- Max16Text_T2S_1 | Reference of the instruction provided by a Third Party | Only one reference must be provided per occurrence of linkages block. | | 0..1 |
| 57 | BE | Reference Owner BIC | VARCHAR (11) | BIC of the reference's owner | Must occur when one of the following fields is present: ■ Securities Settlement Transaction Id | | 0..1 |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|-------------------------------------|--------------|----------------------------------|------------------|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| | | | | | <ul style="list-style-type: none"> ■ IntraPosition-Movement Id ■ IntraBalanceMovement Id ■ AccountService Transaction Id ■ Pool Id ■ Other Transaction Id | | |
| Group "Trade Transaction Condition" | | | | | | 0..1 | |
| 58 | BF | Trade Transaction Condition Code | Possible values: | Trade Transaction Code: | <ul style="list-style-type: none"> ■ BCBL ■ BCBN ■ BCFD ■ BCPD ■ BCRO ■ BCRP ■ CBNS ■ CCPN | | 1..1 |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| | | | <ul style="list-style-type: none"> CDIV CRTS CWAR GTDL MAPR NEGO NMPR SPCU SPEX XBNS XCPN XDIV XRTS XWAR | <ul style="list-style-type: none"> BCRO = Result-Option BCRP = Result-Repo CBNS = CumBonus CCPN = Cum-Coupon CDIV = CumDividend CRTS = Cum-Rights CWAR = Cum-Warrant GTDL = GuaranteedDelivery MAPR = Market-Price NEGO = NegotiatedTrade NMPR = NonMarketPrice | | | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-------------------|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| | | | | <ul style="list-style-type: none"> ■ SPCU = Special-CumDividend ■ SPEX = SpecialExDividend ■ XBNS = ExBonus ■ XCPN = Ex-Coupon ■ XDIV = ExDividend ■ XRTS = ExRights ■ XWAR = ExWarrant | | | |
| | | | | | | 0..2 | |
| 59 | BG | Hold Status Types | Possible values: | <p>Type of hold:</p> <ul style="list-style-type: none"> ■ CSDH = CSD Hold only the instructed leg is put on CSD Hold ■ PTYH = only the instructed leg is put on PartyHold | <ul style="list-style-type: none"> ■ At least one occurrence must be present if Hold Indicator is set to true ■ If the hold indicator is set to false or empty, the Hold Status | | 0..1 |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-------------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| | | | | <ul style="list-style-type: none"> ■ PRCY = only the T2S generated counterleg is put on Party Hold ■ BOTH = both legs are put on Party Hold | <p>Types column must not be present.</p> <ul style="list-style-type: none"> ■ If more than one Hold Reason occurs, the same value cannot be repeated within the same Instruction. ■ Only the following combinations within the same instruction are possible: <ul style="list-style-type: none"> – CSDH and PTYH – CSDH and PRCY – CSDH and BOTH | | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-------------|--------|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| | | | | | <ul style="list-style-type: none"> ■ For an unmatched settlement instruction only the following codes for the Hold indicator are allowed: <ul style="list-style-type: none"> ■ CSDH ■ PTYH ■ For an already matched settlement instruction (i.e. if field Already matched instruction has value MACH) the following codes for the Hold indicator are allowed: <ul style="list-style-type: none"> – CSDH – PTYH – PRCY | | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------------------------------|--------------|----------------------------------|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|-------------------|------------------|
| | | | | | – BOTH | | |
| Group "Settlement Transaction Condition" | | | | | | 0..3 | |
| 60 | BH | Settlement Transaction Condition | Possible values: | Settlement Transaction Condition Code: <ul style="list-style-type: none"> ■ ADEA ■ ASGN ■ BSSP ■ BUTC ■ CLEN ■ DIRT ■ DLWM ■ DRAW ■ EXER ■ EXPI ■ FRCL ■ KNOC ■ NOMC ■ PENS ■ PHYS ■ RESI | | | 1..1 |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------|------------------|
| | | | <ul style="list-style-type: none"> ■ RHYP ■ RPTO ■ SHOR ■ SPDL ■ SPST ■ TRAN ■ TRIP ■ UNEX | <ul style="list-style-type: none"> ■ EXPI = Expired ■ FRCL = Free-CleanSettlement ■ KNOC = KnockedOut ■ NOMC = NoAutomaticMarketClaim ■ PENS = Pending-Sale ■ PHYS = Physical ■ RESI = Residual ■ RHYP = Rehypothecation ■ RPTO = Reporting ■ SHOR = ShortSell ■ SPDL = SpecialDelivery ■ SPST = SplitSettlement | | | |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|-------------------------------------------------|----------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| | | | | <ul style="list-style-type: none"> ■ TRAN = Transformation ■ TRIP = Tri-partySegregation ■ UNEX = Unexposed | | | |
| 61 | BI | Place of Trade ID- Market Identifier Code | Text [A-Z0-9]{4,4} | | <p>If the "Place of Trade ID- Market Identifier Code" is filled in, then "Place of Trade ID- Description" cannot be filled in.</p> <p>If the "Place of Trade ID- Market Identifier Code" is filled in, a value for the "Place of Trade Type- Code" must be filled in.</p> | 0..1 | 0..1 |
| 62 | BJ | Place of Trade ID- Description | Text{1,30} ([0-9a-zA-Z\-\?\:\(\)\,\,\+\,]([0-9a-zA-Z\-\?\:\(\)\,\,\+\,] | | <p>If the "Place of Trade ID- Description" is filled in, then "Place</p> | 0..1 | 0..1 |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|---------------------------|------------------------------------------------------------------------------|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| | | |]*([0-9a-zA-Z\-\?:\\(\.\,\'\+])?)*) | | of Trade ID- Market Identifier Code" can- not be filled in. If the "Place of Trade ID- Description" is filled in, a value for the "Place of Trade Type- Code" must be filled in. | | |
| 63 | BK | Place of Trade Type- Code | Possible values: PRIM SECM OTCO VARI EXCH | | If the "Place of Trade ID- Market Identifier Code" or "Place of Trade ID- Description" is filled in, a value for the "Place of Trade Type- Code" must be filled in | 1..1 | 1..1 |
| 64 | BL | Place of clearing | VARCHAR (11) Text [A-Z]{6,6}[A- Z2-9][A- NP- Z0-9] ([AZ0-9]{3,3}){0,1} | | Shows the BIC code of the Clearing House involved in the settle- ment (if any). | 0..1 | 0..1 |

| Flat file column | Excel Column | Column Name | Format | Description | Rules | Occurs per Record | Occurs per Group |
|------------------|--------------|----------------------|-----------------------------------|-------------|------------------------------------------------------------|-------------------|------------------|
| 65 | BM | Beneficial Ownership | Possible values: ■ YES ■ NO | | Specifies whether there is change of Beneficial Ownership. | 0..1 | 0..1 |

RestrictedFINMax16Text_T2S_1 :

■ Pattern: [0-9a-zA-Z|-|?:|(||.|'|+|)|/?([0-9a-zA-Z|-|?:|(||.|'|+|)|/?)*[0-9a-zA-Z|-|?:|(||.|'|+|)+|?)

3.2 Format of "Enriched Files"

The format of the enriched files is based on the format of the Excel and the flat files that have been submitted to DMT. The submitted data remains unchanged but is supplemented with "Further Notifications" and "Statistical Information".

3.2.1 Further Notifications for Static Data records

This data appears in the first row of each Static Data record. It is located right to the migration data.

| Flat file column | Excel Column | Field | Format | Description | Rules | Occurs per Record |
|------------------|--------------|------------|--------------------------------------------------|--------------------------|---------------------------------------|-------------------|
| last +1 | last +1 | Status | Possible values: ■ Migrated ■ Not migrated | Status of the migration. | n/a | 1..1 |
| last +2 | last +2 | Error Code | CHAR (4) | Code of the error. | Occurs when Status is 'Not migrated'. | 0..1 |

| Flat file column | Excel Column | Field | Format | Description | Rules | Occurs per Record |
|------------------|--------------|---------------------|---------------|---------------------------|---------------------------------------|-------------------|
| last +3 | last +3 | Error Description | VARCHAR (210) | Description of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +4 | last +4 | Error Code 2 | CHAR (4) | Code of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +5 | last +5 | Error Description 2 | VARCHAR (210) | Description of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +6 | last +6 | Error Code 3 | CHAR (4) | Code of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +7 | last +7 | Error Description 3 | VARCHAR (210) | Description of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +8 | last +8 | Error Code 4 | CHAR (4) | Code of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +9 | last +9 | Error Description 4 | VARCHAR (210) | Description of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +10 | last +10 | Error Code 5 | CHAR (4) | Code of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +11 | last +11 | Error Description 5 | VARCHAR (210) | Description of the error. | Occurs when Status is 'Not migrated'. | 0..1 |

■ "last" stands for the last column with migration data

3.2.2 Further Notifications for Free of Payment Settlement Instruction and Pending Instructions records

This data appears in the first row of each Free of Payment Settlement Instruction or Pending Instructions record. It is located right to the migration data.

| Flat file column | Excel Column | Field | Format | Description | Rules | Occurs per Record |
|------------------|--------------|---------------------|--------------------------------------------------|---------------------------------------------|---------------------------------------|-------------------|
| last +1 | last +1 | Status | Possible values: ■ Migrated ■ Not migrated | Status of the migration. | n/a | 1..1 |
| last +2 | last +2 | T2S Reference DELI | VARCHAR (16) | T2S Reference of the delivering instruction | Occurs when Status is 'Migrated'. | 0..1 |
| last +3 | last +3 | T2S Reference RECE | VARCHAR (16) | T2S Reference of the receiving instruction | Occurs when Status is 'Migrated'. | 0..1 |
| last +4 | last +4 | Error Code | CHAR (4) | Code of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +5 | last +5 | Error Description | VARCHAR (210) | Description of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +6 | last +6 | Error Code 2 | CHAR (4) | Code of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +7 | last +7 | Error Description 2 | VARCHAR (210) | Description of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +8 | last +8 | Error Code 3 | CHAR (4) | Code of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +9 | last +9 | Error Description 3 | VARCHAR (210) | Description of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +10 | last +10 | Error Code 4 | CHAR (4) | Code of the error. | Occurs when Status is 'Not migrated'. | 0..1 |

| Flat file column | Excel Column | Field | Format | Description | Rules | Occurs per Record |
|------------------|--------------|---------------------|---------------|---------------------------|---------------------------------------|-------------------|
| last +11 | last +11 | Error Description 4 | VARCHAR (210) | Description of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +12 | last +12 | Error Code 5 | CHAR (4) | Code of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +13 | last +13 | Error Description 5 | VARCHAR (210) | Description of the error. | Occurs when Status is 'Not migrated'. | 0..1 |

- "last" stands for the last column with migration data
- For accepted already matched instructions "T2S Reference DELI" and "T2S Reference RECE" is informed.
- For accepted unmatched instructions, depending on the movement type the corresponding T2S reference column is informed (either "T2S Reference DELI" or "T2S Reference RECE").

3.2.3 Further Notifications for Settlement Restriction records

This data appears in the first row of each Settlement Restriction record. It is located right to the migration data.

| Flat file column | Excel Column | Field | Format | Description | Rules | Occurs per Record |
|------------------|--------------|---------------|--------------------------------------------------|----------------------------------|---------------------------------------|-------------------|
| last +1 | last +1 | Status | Possible values: ■ Migrated ■ Not migrated | Status of the migration. | n/a | 1..1 |
| last +2 | last +2 | T2S Reference | VARCHAR (16) | T2S Reference of the restriction | Occurs when Status is 'Migrated'. | 0..1 |
| last +3 | last +3 | Error Code | CHAR (4) | Code of the error. | Occurs when Status is 'Not migrated'. | 0..1 |

| Flat file column | Excel Column | Field | Format | Description | Rules | Occurs per Record |
|------------------|--------------|---------------------|---------------|---------------------------|---------------------------------------|-------------------|
| last +4 | last +4 | Error Description | VARCHAR (210) | Description of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +5 | last +5 | Error Code 2 | CHAR (4) | Code of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +6 | last +6 | Error Description 2 | VARCHAR (210) | Description of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +7 | last +7 | Error Code 3 | CHAR (4) | Code of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +8 | last +8 | Error Description 3 | VARCHAR (210) | Description of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +9 | last +9 | Error Code 4 | CHAR (4) | Code of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +10 | last +10 | Error Description 4 | VARCHAR (210) | Description of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +11 | last +11 | Error Code 5 | CHAR (4) | Code of the error. | Occurs when Status is 'Not migrated'. | 0..1 |
| last +12 | last +12 | Error Description 5 | VARCHAR (210) | Description of the error. | Occurs when Status is 'Not migrated'. | 0..1 |

■ "last" stands for the last column with migration data

3.2.4 Statistical Information

This data appears in the 2nd row of the spreadsheet. It is located right to the further notifications.

| Flat file column | Excel Column | Field | Format | Description | Rules | Occurs per Record |
|------------------|--------------|--------------|--------------|----------------------------------------------------------------------|-------|-------------------|
| last +12 | last +12 | Submitted | NUMERIC (10) | Total number of records submitted. | n/a | 1..1 |
| last +13 | last +13 | Migrated | NUMERIC (10) | Total number of records that have been migrated successfully. | n/a | 1..1 |
| last +14 | last +14 | Not Migrated | NUMERIC (10) | Total number of records that have not been migrated due to an error. | n/a | 1..1 |

■ "last" stands for the last column with migration data

3.3 Format of Delta Files

The format of the delta files is the same as the format of the Excel and the flat files. The difference is that those records that have been migrated successfully are dropped from the submitted file. The remaining records shall be edited and the file could be submitted again.